

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 1

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

SECTION 1. IDENTIFICATION

Identification of the company:	Avient Colorants Canada Inc. 2 Lone Oak Court Toronto, Ontario, M9C 5R9 Telephone No.: +1 514-832-2559
	Information of the substance/preparation: Product Stewardship e-mail: SDS.NORAMMB@avient.com
	Emergency tel. number: +1 CANUTEC (613) 996-6666

Trade name:	ABSA 004.000% GRAPHITE
Material number:	SB74653634
Chemical family:	Colourant preparation Carrier: ABS
Primary product use:	Additive for plastic material processing

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Hazards Not Otherwise Classified:

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Colourant preparation
Carrier: ABS

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Iron(III)oxide	Iron(III)oxide	1309-37-1	0.1 - 1
Aluminium oxide	Aluminium oxide	1344-28-1	0.1 - 1
Styrene	styrene	100-42-5	0.1 - 1
C.I. Pigment Black 7	C.I. Pigment Black 7	1333-86-4	1 - 5

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 2

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

C.I. Pigment Brown 24	antimony compounds	68186-90-3	10 - 30
C.I. Pigment White 6	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	13463-67-7	10 - 30
2-Propenenitrile, polymer with ethenylbenzene	2-Propenenitrile, polymer with ethenylbenzene	9003-54-7	30 - 60

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and by the Canadian WHMIS 2015 Hazardous Products Regulations (SOR/2015-17)., The hazardous ingredients of this product are encapsulated, therefore the material is not GHS classified for health and environmental hazards as exposure is not expected., Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

- If inhaled : Move the victim to fresh air.
Give oxygen or artificial respiration if needed.
Get immediate medical advice/ attention.
Never give anything by mouth to an unconscious person.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
In case of burns apply cold water until pain subsides then seek medical advice.
Burns must be treated by a physician.
If molten polymer contacts the skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burn. Skin absorption of reground pellets is unlikely.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Get medical attention immediately if irritation develops and persists.
- If swallowed : Rinse mouth.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
Get medical advice/ attention.
- Most important symptoms and effects, both acute and delayed : The possible symptoms known are those derived from the labelling (see section 2).
No additional symptoms are known.
- Notes to physician : Treat symptomatically.

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 3

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : In case of fire hazardous decomposition products may be produced such as:
Styrene
Hydrogen cyanide (hydrocyanic acid)
Acrylonitrile
Carbon monoxide
Carbon dioxide (CO₂)
Metal oxides
Sulphur oxides
Carbon monoxide and carbon dioxide
Styrene
Hydrocarbons
Oxides of phosphorus
Take measures to prevent the build up of electrostatic charge.
Dust can form an explosive mixture in air.
- Further information : Combustible material
In the event of fire and/or explosion do not breathe fumes.
During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion
Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Do not allow run-off from fire fighting to enter drains or water courses.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
Avoid contact with skin, eyes and clothing.
Wash thoroughly after handling.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent product from entering drains.

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 4

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Methods and materials for containment and cleaning up : Avoid dust formation.
Take measures to prevent the build up of electrostatic charge.
Sweep up and shovel into suitable containers for disposal.
Take up uncontaminated material and pass on for further processing.
After cleaning, flush away traces with water.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take measures to prevent the build up of electrostatic charge.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Use only with adequate ventilation/personal protection.
For personal protection see section 8.
Avoid contact with skin, eyes and clothing.
Use only with adequate ventilation.
When handling hot melts use suitable protective clothing.
Avoid dust formation. Keep away from sources of ignition.
Lead off electrostatic charges.

Conditions for safe storage : Keep container tightly closed in a cool, well-ventilated place.
Protect from moisture.
Keep away from direct sunlight.

Further information on storage conditions : Store in a cool, dry, well-ventilated area. Keep container sealed when not in use.
Keep in an area equipped with sprinklers.
Minimize dust generation and accumulation.

Materials to avoid : not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Iron(III)oxide	1309-37-1	TWA (Respirable)	5 mg/m3	CA AB OEL
		TWA (Fumes)	5 mg/m3 (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m3 (Iron)	CA BC OEL
		STEL	10 mg/m3	CA BC OEL

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 5

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

		(Fumes)	(Iron)	
		TWAEV (fume and dust)	5 mg/m3 (Iron)	CA QC OEL
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
Aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
		TWAEV (total dust)	10 mg/m3 (Aluminium)	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	CA BC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH
C.I. Pigment Brown 24	68186-90-3	TWA	0.5 mg/m3 (antimony)	CA AB OEL
		TWAEV	0.5 mg/m3 (antimony)	CA QC OEL
		TWA	0.5 mg/m3 (antimony)	CA BC OEL
		TWA	0.5 mg/m3 (antimony)	ACGIH
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
C.I. Pigment Black 7	1333-86-4	TWA	3.5 mg/m3	CA AB OEL
		TWA (Inhalable)	3 mg/m3	CA BC OEL
		TWAEV (inhalable dust)	3 mg/m3	CA QC OEL
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
C.I. Pigment White 6	13463-67-7	TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Styrene	100-42-5	TWA	20 ppm 85 mg/m3	CA AB OEL
		STEL	40 ppm	CA AB OEL

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 6

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

			170 mg/m3	
		TWA	20 ppm	CA BC OEL
		STEL	40 ppm	CA BC OEL
		TWA	35 ppm	CA ON OEL
		STEL	100 ppm	CA ON OEL
		STEV	100 ppm 426 mg/m3	CA QC OEL
		TWAEV	50 ppm 213 mg/m3	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	20 ppm	ACGIH

Engineering measures : Use only in area provided with appropriate exhaust ventilation.
Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.
Use engineering controls such as local or general exhaust to maintain airborne concentrations below exposure limits.

Personal protective equipment

Respiratory protection : Use NIOSH/MSHA approved respirators following manufacturer's recommendations where dust or fume may be generated.
Use respiratory protective equipment when using this product at elevated temperatures (see section 8).

Hand protection
Remarks : Nitrile rubber gloves. Impervious butyl rubber gloves PVC Neoprene gloves When handling hot material, use heat resistant gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : Wear protective clothing, including long sleeves and gloves, to prevent skin contact.
When handling hot melts use suitable protective clothing.

Hygiene measures : The usual Industrial Hygiene precautions must be taken during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during work intervals and after work.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Granules

Colour : grey

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 7

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Odour	:	characteristic
Odour Threshold	:	Not applicable
pH	:	Not applicable
Melting point	:	> 90 °C
Boiling point	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	not determined
Self-ignition	:	Not applicable
Upper explosion limit / upper flammability limit	:	not tested.
Lower explosion limit / Lower flammability limit	:	not tested.
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	not available
Density	:	approx. 1.1 g/cm ³ Value determined from data on raw material.
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	This property is not applicable for mixtures.
Decomposition temperature	:	To the best of our current knowledge, no thermal decomposition of the product is expected if it is processed according to good manufacturing practices. See section 10.4. "Conditions to avoid"
Viscosity Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Explosive properties	:	no data available

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 8

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

no data available

Oxidizing properties : not available
Surface tension : Not relevant
Particle size : Product specific

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : To avoid thermal decomposition, do not overheat.
Heating can release hazardous gases.
Keep away from heat, sparks, open flames, and other sources of ignition.
If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Keep away from strong bases.
Strong oxidizing agents

Incompatible materials : Strong oxidizing agents
Oxidizing agents

Hazardous decomposition products : No decomposition if used as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

None known.

Acute toxicity

Components:

Styrene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 9

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

C.I. Pigment Brown 24:

Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg
Method: BASF test
GLP: no

Acute inhalation toxicity : Remarks: Not applicable

Acute dermal toxicity : Remarks: Not applicable

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

Styrene:

Result: Irritating to skin.

C.I. Pigment Brown 24:

Species: Rabbit
Exposure time: 24 h
Method: Draize Test
Result: No skin irritation
GLP: no

Serious eye damage/eye irritation

Product:

Result: No eye irritation

Components:

Styrene:

Result: Irritating to eyes.

C.I. Pigment Brown 24:

Species: rabbit eye
Result: slight irritation
Method: FDA guideline
GLP: no

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 10

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

Styrene:

Result: Does not cause skin sensitisation.

C.I. Pigment Brown 24:

Remarks: Not applicable

Germ cell mutagenicity

Components:

Styrene:

Genotoxicity in vitro : Remarks: no data available

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

C.I. Pigment Brown 24:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Concentration: 100 - 5000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Ames test
Test system: Escherichia coli
Concentration: 2,5 - 5000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Concentration: 0,5 - 900 µg/ml
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative
GLP: yes

Test Type: In vitro gene mutation study in mammalian cells
Test system: mouse lymphoma cells

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 11

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Concentration: 3,13 - 100 µg/ml
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : It is concluded that the product is not mutagenic based on evaluation of several mutagenicity tests.

Carcinogenicity

Components:

Styrene:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

C.I. Pigment Brown 24:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

Styrene:

Effects on fertility : Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

C.I. Pigment Brown 24:

Effects on fertility : Test Type: One generation study
Species: Rat, male and female
Strain: Sprague-Dawley
Application Route: oral (gavage)
Dose: 250 - 500 - 1000 mg/kg
General Toxicity - Parent: NOAEL: \geq 1,000 mg/kg body weight
General Toxicity F1: NOAEL: \geq 1,000 mg/kg body weight
Method: OECD Test Guideline 422
GLP: yes

Effects on foetal development : Species: Rat
Strain: Sprague-Dawley
Application Route: oral (gavage)
Dose: 250 - 500 - 1000 mg/kg
General Toxicity Maternal: NOAEL: \geq 1,000 mg/kg body weight
Teratogenicity: NOAEL: \geq 1,000 mg/kg body weight

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 12

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Method: OECD Test Guideline 422
GLP: yes

Reproductive toxicity - : No reproductive toxicity to be expected.
Assessment : No teratogenic effects to be expected.

STOT - single exposure

Components:

Styrene:

Assessment: May cause respiratory irritation.

C.I. Pigment Brown 24:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

Styrene:

Target Organs: hearing organs

Assessment: Causes damage to organs through prolonged or repeated exposure.

C.I. Pigment Brown 24:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

Styrene:

Remarks: This information is not available.

C.I. Pigment Brown 24:

Species: Rat, male and female

NOAEL: 500 mg/kg

Application Route: oral (feed)

Exposure time: 90 d

Number of exposures: daily

Dose: 0,5 - 5 - 50 - 500 mg/kg

Group: yes

Method: OECD Test Guideline 408

GLP: No information available.

Application Route: Inhalation

Remarks: not tested.

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 13

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Application Route: Skin contact
Remarks: not tested.

Aspiration toxicity

Components:

Styrene:

May be fatal if swallowed and enters airways.

C.I. Pigment Brown 24:

No aspiration toxicity classification

Experience with human exposure

Product:

General Information : The possible symptoms known are those derived from the labelling (see section 2).

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: no data available

Components:

Styrene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.02 mg/l
Exposure time: 96 h
Method: Other

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 4.9 mg/l
Exposure time: 72 h
Test Type: static test
Method: Other

Toxicity to fish (Chronic toxicity) : Remarks: no data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: no data available

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 14

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Toxicity to microorganisms : EC50 (Bacteria): 500 mg/l
Exposure time: 0.5 h

Toxicity to soil dwelling organisms : Remarks: Not applicable

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial organisms : Remarks: Not applicable

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

C.I. Pigment Brown 24:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Method: DIN 38412 T.15
GLP: no
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 202
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 201
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to fish (Chronic toxicity) : Remarks: not required

Toxicity to daphnia and other : Remarks: not required

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 15

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

aquatic invertebrates
(Chronic toxicity)

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 10,000 mg/l
End point: Bacteria toxicity (respiration inhibition)
Exposure time: 0.5 h
Test Type: aquatic
Analytical monitoring: no
Method: DIN 38412 T.27
GLP: no
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to soil dwelling organisms : Remarks: Not applicable

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial organisms : Remarks: Not applicable

C.I. Pigment White 6:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Persistence and degradability

Components:

Styrene:

Biodegradability : aerobic
Result: Readily biodegradable.
Biodegradation: 70.9 %
Exposure time: 28 d

C.I. Pigment Brown 24:

Biodegradability : Remarks: Not applicable for inorganic compound.

Physico-chemical removability : Remarks: Inorganic product, cannot be eliminated from the water by biological purification processes.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: not tested.

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 16

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Components:

Styrene:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

C.I. Pigment Brown 24:

Bioaccumulation : Remarks: Not relevant for inorganic substances

C.I. Pigment White 6:

Partition coefficient: n-octanol/water : Remarks: inorganic

Mobility in soil

Product:

Distribution among environmental compartments : Remarks: not tested.

Components:

Styrene:

Distribution among environmental compartments : Remarks: no data available

C.I. Pigment Brown 24:

Distribution among environmental compartments : Remarks: Not applicable

Other adverse effects

Product:

Results of PBT and vPvB assessment : Remarks: No information is available as no chemical safety report (CSR) is required.

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

Components:

Styrene:

Environmental fate and pathways : no data available

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 17

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

C.I. Pigment Brown 24:

Environmental fate and pathways : not available

Results of PBT and vPvB assessment : The substance is inorganic, thus a PBT and vPvB criteria assessment is not applicable according to Annex XIII of Regulation (EC) 1907/2006.

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of this product in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Regulations concerning reuse or disposal of used packaging materials must be observed.

SECTION 14. TRANSPORT INFORMATION

TDG not restricted

IATA not restricted

IMDG not restricted

SECTION 15. REGULATORY INFORMATION

NPRI Components : Chromium (III) compound
Antimony compounds
Styrene

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 18

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA ON OEL / STEL	:	Short-Term Exposure Limit (STEL)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

SAFETY DATA SHEET



ABSA 004.000% GRAPHITE

Page 19

Substance key: 000000915732

Revision Date: 04/20/2022

Version : 1 - 0 / CDN

Date of printing :02/13/2025

Revision Date : 04/20/2022
Date format : mm/dd/yyyy

The information contain herein is accurate to the best knowledge of Avient Corporation and its subsidiaries and affiliates. However, neither Avient nor any of its subsidiaries or affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of the Avient product is the sole responsibility of the user. Any material may present unknown hazards and should be used with caution. Due to possible changes in Avient products and applicable national and international regulations and laws, the status of the products could change. Although certain hazards are described herein, Avient and its subsidiaries and affiliates cannot guarantee that these are the only hazards that exist. This information is only valid for the current intended use, and is not valid for such Avient product used in conjunction with any other materials or in any process.

CA / EN