

EVA 003.000% FE 3922 BEIGE

Page 1

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025

SECTION 1. IDENTIFICATION

Identification of the	Avient Colorants Canada Inc.
company:	2 Lone Oak Court
	Toronto, Ontario, M9C 5R9
	Telephone No.: +1 514-832-2559
	Information of the substance/preparation:
	Product Stewardship
	e-mail: SDS.NORAMMB@avient.com
	Emergency tel. number: +1 CANUTEC (613) 996-6666
Trade name: Material number:	EVA 003.000% FE 3922 BEIGE PR83754430
Chemical family:	Colourant preparation Carrier: crosslinked PE

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Hazards Not Otherwise Classified: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Colourant preparation Carrier: crosslinked PE

Components

Chemical name	CAS-No.	Concentration (% w/w)
C.I. Pigment Black 28	68186-91-4	0.1 - 1
Aluminium oxide	1344-28-1	0.1 - 1
Calcium carbonate	471-34-1	0.1 - 1
Vinyl acetate	108-05-4	0.1 - 1
C.I. Pigment White 6	13463-67-7	30 - 60

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and by the Canadian WHMIS 2015 Hazardous Products Regulations (SOR/2015-17)., The hazardous ingredients of this product are encapsulated, therefore the material is not



EVA 003.000% FE 3922 BEIGE

Page 2

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025

GHS classified for health and environmental hazards as exposure is not expected., Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move the victim to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical advice/ attention. Never give anything by mouth to an unconscious person.
In case of skin contact	:	Wash off immediately with plenty of water for at least 15 minutes. In case of burns apply cold water until pain subsides then seek medical advice. Burns must be treated by a physician. If molten polymer contact the skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burn. Skin absorption of reground pellets is unlikely.
In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately if irritation develops and persists.
If swallowed	:	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/ attention.
Most important symptoms and effects, both acute and delayed	:	The possible symptoms known are those derived from the labelling (see section 2). No additional symptoms are known.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide Carbon dioxide (CO2) Avoid generating dust; fine dust dispersed in air in sufficient



EVA 003.000% FE 3922 BEIGE

Page 3

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
Further information :	concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Metal oxides
	In the event of fire and/or explosion do not breathe fumes. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Do not allow run-off from fire fighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment : for firefighters	Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.
Environmental precautions	:	Do not allow contact with soil, surface or ground water. Prevent product from entering drains.
Methods and materials for containment and cleaning up	:	Avoid dust formation. Take measures to prevent the build up of electrostatic charge. Sweep up and shovel into suitable containers for disposal. Take up uncontaminated material and pass on for further processing. After cleaning, flush away traces with water.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Take measures to prevent the build up of electrostatic charge.
Advice on safe handling	:	 Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation/personal protection. For personal protection see section 8. Avoid contact with skin, eyes and clothing. Use only with adequate ventilation. When handling hot melts use suitable protective clothing. Avoid dust formation. Keep away from sources of ignition. Lead off electrostatic charges.
• ··· · ·		

Conditions for safe storage : Keep container tightly closed in a cool, well-ventilated place.



EVA 003.000% FE 3922 BEIGE

Page 4

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
Further information on : storage conditions	Protect from moisture. Keep away from direct sunlight. Store in a cool, dry, well-ventilated area. Keep container sealed when not in use.
Materials to avoid :	Keep in an area equipped with sprinklers. Minimize dust generation and accumulation. not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
C.I. Pigment Black 28	68186-91-4	TWA	1 mg/m3 (Copper)	NIOSH REL
C.I. Pigment White 6	13463-67-7	TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
Aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
		TWAEV (total dust)	10 mg/m3 (Aluminium)	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	CA BC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH
Calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m3	CA QC OEL
Vinyl acetate	108-05-4	TWA	10 ppm 35 mg/m3	CA AB OEL
		STEL	15 ppm 53 mg/m3	CA AB OEL
		TWA	10 ppm	CA BC OEL
		STEL	15 ppm	CA BC OEL
		TWAEV	10 ppm 35 mg/m3	CA QC OEL
		STEV	15 ppm 53 mg/m3	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH

Engineering measures : Use only in area provided with appropriate exhaust



EVA 003.000% FE 3922 BEIGE

Page 5

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
	ventilation.
	Provide appropriate exhaust ventilation at machinery and at
	places where dust can be generated.

Use engineering controls such as local or general exhaust to maintain airborne concentrations below exposure limits.

Personal protective equipment

Respiratory protection	Use NIOSH/MSHA approved respirators following manufacturer's recommendations where dust or fume may b generated. Use respiratory protective equipment when using this produc at elevated temperatures (see section 8).	
Hand protection		
Remarks	Nitrile rubber gloves. Impervious butyl rubber gloves PVC Neoprene gloves When handling hot material, use heat resistant gloves.	
Eye protection :	Safety glasses with side-shields	
Skin and body protection	Wear protective clothing, including long sleeves and gloves,	
	to prevent skin contact. When handling hot melts use suitable protective clothing.	
Hygiene measures	The usual Industrial Hygiene precautions must be taken during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during work intervals and after work.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Granules
Colour	:	brown
Odour	:	characteristic
Odour Threshold	:	Not applicable
рН	:	Not applicable
Melting point	:	Not applicable
Boiling point	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable



EVA 003.000% FE 3922 BEIGE

Page 6

stance key: 000000781249		Revision Date: 09/21/2020
sion : 1 - 1 / CDN		Date of printing :01/24/202
Flormachility (collidered)		not dotormined
Flammability (solid, gas)	:	not determined
Self-ignition	:	Not applicable
Upper explosion limit / upper flammability limit	:	not tested.
Lower explosion limit / Lower flammability limit	:	not tested.
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	not available
Density	:	not tested.
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	This property is not applicable for mixtures.
Decomposition temperature	:	To the best of our current knowledge, no thermal decomposition of the product is expected if it is processed according to good manufacturing practices. See section 10.4. "Conditions to avoid"
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Explosive properties	:	no data available no data available
Oxidizing properties	:	not available
Surface tension	:	Not relevant
Particle size	:	Product specific

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.



EVA 003.000% FE 3922 BEIGE

Page 7

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Heating can release hazardous gases.
	Keep away from heat, sparks, open flames, and other sources of ignition.
	If small particles are generated during further processing, handling or by other means, may form combustible dust
	concentrations in air. Dust deposits should not be allowed to accumulate on
	surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Incompatible materials	: none
	Strong oxidizing agents Halogenated hydrocarbons
Hazardous decomposition	: No hazardous decomposition products if stored and handled
products	as prescribed

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure None known.		
Acute toxicity		
Product:		
Acute inhalation toxicity	:	Acute toxicity estimate: 16.94 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Components:		
Aluminium oxide:		
Acute oral toxicity	:	LD50 (Rat, male and female): > 10,000 mg/kg Method: OECD Test Guideline 401 GLP: No information available.
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 2.3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: yes Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	Remarks: Not applicable
Vinyl acetate:		
Acute inhalation toxicity	:	Assessment: The component/mixture is moderately toxic after short term inhalation.



EVA 003.000% FE 3922 BEIGE

Page 8

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
C.I. Pigment White 6:	
Acute oral toxicity :	LD50 (Rat, female): > 5,000 mg/kg Method: OECD Test Guideline 425 GLP: no
Acute inhalation toxicity :	LC50 (Rat, male and female): 3.4 - 5.1 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: no Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity :	Assessment: The substance or mixture has no acute dermal toxicity Remarks: not required

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

Aluminium oxide:

Species: Rabbit Exposure time: 24 h Method: OECD Test Guideline 404 Result: No skin irritation GLP: No information available.

C.I. Pigment White 6:

Species: Rabbit Exposure time: 4 h Method: OECD Test Guideline 404 Result: No skin irritation GLP: no

Serious eye damage/eye irritation

Product: Result: No eye irritation

Components:

Aluminium oxide: Result: Mild eye irritation

C.I. Pigment White 6:

Species: rabbit eye Result: No eye irritation

EVA 003.000% FE 3922 BEIGE

Substance key: 000000781249 Version : 1 - 1 / CDN

> Method: OECD Test Guideline 405 GLP: No information available.

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

Aluminium oxide:

Test Type: Draize Test Exposure routes: Dermal Species: Guinea pig Method: Draize Test Result: Not a skin sensitizer. GLP: no

Test Type: Respiratory system Exposure routes: inhalation (dust/mist/fume) Species: Mouse Method: Other Result: Not a skin sensitizer. GLP: no

C.I. Pigment White 6:

Test Type: Local lymph node assay (LLNA) Exposure routes: Dermal Species: Mouse Method: OECD Test Guideline 429 Result: Not a skin sensitizer. GLP: No information available.

Test Type: Buehler Test Exposure routes: Dermal Species: Guinea pig Method: OECD Test Guideline 406 Result: Not a skin sensitizer. GLP: yes

Test Type: Respiratory system Exposure routes: inhalation (dust/mist/fume) Species: Mouse Method: Other Result: Does not cause respiratory sensitisation. GLP: No information available.

Germ cell mutagenicity

Components:

Aluminium oxide:

Genotoxicity in vitro

: Test Type: In vitro gene mutation study in mammalian cells



Page 9

Revision Date: 09/21/2020 Date of printing :01/24/2025



EVA 003.000% FE 3922 BEIGE

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
	Test system: mouse lymphoma cells Concentration: 6,1 - 780 µg/ml Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative GLP: yes Remarks: By analogy with a product of similar composition
Genotoxicity in vivo	Test Type: Chromosome Aberration Test Species: Rat (female) Strain: wistar Cell type: Bone marrow Application Route: oral (gavage) Exposure time: Single exposure Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 475 Result: positive GLP: No information available. Test Type: Micronucleus test Species: Rat (female) Strain: wistar Cell type: Bone marrow Application Route: oral (gavage) Exposure time: Single exposure Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 474 Result: positive GLP: No information available.
Germ cell mutagenicity - Assessment	Weight of evidence does not support classification as a germ cell mutagen.
C.I. Pigment White 6:	
Genotoxicity in vitro	Test Type: Ames test Test system: Salmonella typhimurium Concentration: 333 - 5000 µg/plate Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes
	Test Type: Ames test Test system: Escherichia coli Concentration: 333 - 5000 µg/plate Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes
Genotoxicity in vivo	Test Type: Micronucleus test Species: Mouse (male and female) Strain: ICR



EVA 003.000% FE 3922 BEIGE

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
	Cell type: Erythrocytes Application Route: oral (gavage) Exposure time: single treatment Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 474 Result: negative GLP: yes
Germ cell mutagenicity - : Assessment	In vitro tests did not show mutagenic effects, In vivo tests did not show mutagenic effects
Carcinogenicity	
Components:	
Aluminium oxide:	
Carcinogenicity - : Assessment	Carcinogenicity classification not possible from current data.
Vinyl acetate:	
Carcinogenicity - : Assessment	Suspected human carcinogens
C.I. Pigment White 6:	
Carcinogenicity - : Assessment	Not classifiable as a human carcinogen.
Reproductive toxicity	
Components:	
Aluminium oxide:	
Effects on fertility :	Species: Rat, male and female Strain: Sprague-Dawley Application Route: Drinking water Dose: 57 - 189 - 567 mg/kg General Toxicity - Parent: NOAEL: ca. 567 mg/kg body weight General Toxicity F1: NOAEL: ca. 57 mg/kg body weight Method: Other GLP: yes Remarks: By analogy with a product of similar composition
Effects on foetal : development	Species: Rat Strain: wistar Application Route: oral (gavage) Dose: 126 - 251 - 503 mg/kg Frequency of Treatment: 2 daily General Toxicity Maternal: NOAEL: > 100 mg/kg body weight Teratogenicity: NOAEL: 503 mg/kg body weight Method: OECD Test Guideline 414 GLP: No information available. Remarks: By analogy with a product of similar composition



EVA 003.000% FE 3922 BEIGE

Page 12

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
Reproductive toxicity - : Assessment	No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments. No teratogenic effects to be expected.
C.I. Pigment White 6:	
Effects on fertility	Remarks: no data available
Effects on foetal : development	 Test Type: Pre-natal Species: Rat, female Strain: wistar Application Route: oral (gavage) Dose: 100, 300, 1000 mg/kg bw Duration of Single Treatment: 14 d Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight Developmental Toxicity: NOAEL: 1,000 mg/kg body weight Embryo-foetal toxicity: NOEL: 1,000 mg/kg body weight Method: OECD Test Guideline 414 GLP: yes Remarks: No significant adverse effects were reported
Reproductive toxicity -	No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments. Did not show teratogenic effects in animal experiments.

STOT - single exposure

Components:

Aluminium oxide:

Target Organs: Lungs

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Vinyl acetate:

Exposure routes: Inhalation Target Organs: Respiratory Tract Assessment: May cause respiratory irritation.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

Aluminium oxide:

Target Organs: Lungs Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.



EVA 003.000% FE 3922 BEIGE

Page 13

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

Aluminium oxide:

Species: Rat, male and female NOAEL: 57 mg/kg Application Route: Drinking water Exposure time: 1 a Number of exposures: continuously Dose: 57 - 189 - 567 mg/kg Group: yes Method: OECD Test Guideline 426 GLP: yes Remarks: By analogy with a product of similar composition

Species: Rat LOAEL: 0.070 mg/l Application Route: Inhalation Exposure time: 6 m Number of exposures: 6 hr/day; 5 days a week Dose: 15-30-50-70-100 mg Al/m3 Method: OECD Test Guideline 413 GLP: No information available.

Application Route: Skin contact Remarks: The study is not necessary from a scientific perspective.

C.I. Pigment White 6:

Species: Rat, male NOEL: > 24000 mg/kg bw/day Application Route: oral (gavage) Exposure time: 29 d Number of exposures: daily Dose: 24000 mg/kg Group: yes Method: OECD Test Guideline 407 GLP: No information available.

Species: Rat, male and female NOAEL: 0.01 mg/l Application Route: Inhalation Exposure time: 2 a Number of exposures: 6 hours/day, 5 days/week Dose: 0,0106 - 0,0507 - 0,250 mg/l Group: yes Method: Repeated Dose Toxicity (chronic Toxicity) GLP: no



EVA 003.000% FE 3922 BEIGE

Page 14

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025

Aspiration toxicity

Components:

Aluminium oxide:

No aspiration toxicity classification

C.I. Pigment White 6:

No aspiration toxicity classification

Experience with human exposure

:

Product:

General Information

The possible symptoms known are those derived from the labelling (see section 2).

Further information

Components:

C.I. Pigment White 6:

Remarks: Lung damage possible.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Toxicity to fish :	Remarks: no data available
Components:	
Aluminium oxide:	
Toxicity to fish :	NOEC (Salmo trutta (brown trout)): > 0.072 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other : aquatic invertebrates	NOEC (Daphnia magna (Water flea)): > 0.071 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae/aquatic : plants	NOEC (Pseudokirchneriella subcapitata (green algae)): >= 0.052 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test



EVA 003.000% FE 3922 BEIGE

Substance key: 000000781249	Revision Date: 09/21/2020
/ersion : 1 - 1 / CDN	Date of printing :01/24/2025
	Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes
	EC50 (Pseudokirchneriella subcapitata (green algae)): 1.05 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 201 GLP: yes Remarks: By analogy with a product of similar composition
Toxicity to fish (Chronic toxicity)	 NOEC (Pimephales promelas (fathead minnow)): 56.48 mg/l Exposure time: 7 d Test Type: semi-static test Analytical monitoring: yes Method: Other GLP: yes Remarks: By analogy with a product of similar composition
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	 NOEC (Daphnia magna (Water flea)): 0.076 mg/l End point: Reproduction rate Exposure time: 21 d Test Type: semi-static test Analytical monitoring: yes Method: OECD Test Guideline 211 GLP: yes Remarks: By analogy with a product of similar composition
Toxicity to microorganisms	: Remarks: Not applicable
Toxicity to soil dwelling organisms	: Remarks: Not applicable
Plant toxicity	: Remarks: Not applicable
Sediment toxicity	: Remarks: Not applicable
Toxicity to terrestrial organisms	: Remarks: Not applicable
Ecotoxicology Assessment	
Acute aquatic toxicity	: This product has no known ecotoxicological effects.
Chronic aquatic toxicity	This product has no known ecotoxicological effects.
C.I. Pigment White 6: Toxicity to fish	 LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no

EVA 003.000% FE 3922 BEIGE



Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
	Method: EPA GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
	Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration.
	LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to daphnia and other : aquatic invertebrates	LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal concentration.
	LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Method: ISO 14669 and PARCOM method GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to algae/aquatic : plants	EC50 (Pseudokirchneriella subcapitata (microalgae)): 61 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no Method: EPA GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration.
	EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l End point: Growth rate Exposure time: 72 h



EVA 003.000% FE 3922 BEIGE

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
	Analytical monitoring: no data available Method: ISO 10253 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to fish (Chronic : toxicity)	LC50 (Oncorhynchus mykiss (rainbow trout)): 7.31 mg/l Exposure time: 28 d Test Type: static test Analytical monitoring: yes Method: Other GLP: No information available. Remarks: By analogy with a product of similar composition
Toxicity to microorganisms :	EC50 (activated sludge of a predominantly domestic sewage): > 1,000 mg/l End point: Bacteria toxicity (respiration inhibition) Exposure time: 3 h Test Type: aquatic Method: OECD Test Guideline 209 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
	NOEC (activated sludge of a predominantly domestic sewage): >= 1,000 mg/l End point: Bacteria toxicity (respiration inhibition) Exposure time: 3 h Test Type: aquatic Method: OECD Test Guideline 209 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to soil dwelling : organisms	Test Type: artificial soil NOEC (Folsomia candida): 0,1 ->= 10 % Exposure time: 28 d End point: mortality Method: ISO 11267 GLP: no Remarks: By analogy with a product of similar composition This product does not have any known adverse effect on the soil organisms tested.
Plant toxicity :	NOEC: >= 10 % Exposure time: 20 h End point: Growth Species: Lactuca sativa (lettuce) Analytical monitoring: yes Method: Other GLP: no Remarks: By analogy with a product of similar composition No effect on the growth was observed.



EVA 003.000% FE 3922 BEIGE

stance key: 000000781249 sion : 1 - 1 / CDN		Revision Date: 09/21/20
SIUIT . T - T / GUIN		Date of printing :01/24/20
Sediment toxicity	:	NOEC (Hyalella azteca (Scud)): >= 100000 % Analytical monitoring: no Sediment: artificial soil Exposure duration: 28 d Nominal / Measured: nominal Basis for effect: mortality Method: Other GLP: no Remarks: By analogy with a product of similar composition NOEC: >= 14989 mg/kg dry weight (d.w.) Analytical monitoring: no data available Sediment: Natural sediment Exposure duration: 10 d Nominal / Measured: nominal Basis for effect: mortality Method: Other GLP: yes
Ecotoxicology Assessment		
Chronic aquatic toxicity	:	This product has no known ecotoxicological effects.
Persistence and degradabili	ity	
Components:		
Aluminium oxide:		
Biodegradability	:	Remarks: Not applicable
C.I. Pigment White 6:		
Biodegradability	:	Remarks: Not applicable for inorganic compound.
Bioaccumulative potential		
Product:		
Bioaccumulation	:	Remarks: not tested.
	-	
Components:		
Aluminium oxide:		
Bioaccumulation	:	Remarks: Not applicable
C.I. Pigment White 6:		
Bioaccumulation	:	Species: Oncorhynchus mykiss (rainbow trout) Bioconcentration factor (BCF): 20 - 200 Exposure time: 14 d Concentration: 0.1 - 1 mg/l Method: Other GLP: No information available. Remarks: Does not accumulate in organisms.

EVA 003.000% FE 3922 BEIGE



stance key: 000000781249		Revision Date: 09/21/20
sion : 1 - 1 / CDN		Date of printing :01/24/20
Partition coefficient: n- octanol/water	:	Remarks: inorganic
Mobility in soil		
Product:		
Distribution among environmental compartments	:	Remarks: not tested.
Components:		
Aluminium oxide:		
Distribution among environmental compartments	:	Remarks: Not applicable
C.I. Pigment White 6:		
Mobility	:	Remarks: Adsorption to solid soil phase is possible.
Distribution among environmental compartments	:	Adsorption/Soil Medium: water - soil log Koc: 4.61 Method: Other
Other adverse effects		
Product:		
Results of PBT and vPvB assessment	:	Remarks: No information is available as no chemical safety report (CSR) is required.
Additional ecological information	:	Do not allow to enter ground water, waterways or waste wat
Additional ecological	:	Do not allow to enter ground water, waterways or waste wat
Additional ecological information	:	Do not allow to enter ground water, waterways or waste wat
Additional ecological information	:	Do not allow to enter ground water, waterways or waste wat not available
Additional ecological information Components: Aluminium oxide: Environmental fate and	:	
Additional ecological information Components: Aluminium oxide: Environmental fate and pathways Results of PBT and vPvB	:	not available
Additional ecological information Components: Aluminium oxide: Environmental fate and pathways Results of PBT and vPvB assessment Additional ecological information	:	not available Remarks: Not applicable
Additional ecological information Components: Aluminium oxide: Environmental fate and pathways Results of PBT and vPvB assessment Additional ecological	: :	not available Remarks: Not applicable



EVA 003.000% FE 3922 BEIGE

Page 20

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025
Additional ecological information	Do not allow to enter ground water, waterways or waste water.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Dispose of this product in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Regulations concerning reuse or disposal of used packaging materials must be observed.

SECTION 14. TRANSPORT INFORMATION

TDG	not restricted
ΙΑΤΑ	not restricted
IMDG	not restricted

SECTION 15. REGULATORY INFORMATION

NPRI Components	: Zinc compounds Chromium (III) compound Copper Compound
	Vinyl acetate

The components of this product are reported in the following inventories:DSL:All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH CA AB OEL		USA. ACGIH Threshold Limit Values (TLV) Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL CA QC OEL		Canada. British Columbia OEL Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH REL ACGIH / TWA ACGIH / STEL	:	USA. NIOSH Recommended Exposure Limits 8-hour, time-weighted average Short-term exposure limit



EVA 003.000% FE 3922 BEIGE

NIOSH REL / TWA

Page 21

Substance key: 000000781249	Revision Date: 09/21/2020	
Version : 1 - 1 / CDN	Date of printing :01/24/2025	
CA AB OEL / TWA	: 8-hour Occupational exposure limit	
CA AB OEL / STEL	: 15-minute occupational exposure limit	
CA BC OEL / TWA	8-hour time weighted average	
CA BC OEL / STEL	short-term exposure limit	
CA QC OEL / TWAEV	Time-weighted average exposure value	
CA QC OEL / STEV	Short-term exposure value	

workday during a 40-hour workweek

Time-weighted average concentration for up to a 10-hour

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative: WHMIS - Workplace Hazardous Materials Information System

Revision Date	:	09/21/2020
Date format	:	mm/dd/yyyy

The information contain herein is accurate to the best knowledge of Avient Corporation and its subsidiaries and affiliates. However, neither Avient nor any of its subsidiaries or affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of the Avient product is the sole responsibility of the user. Any material may present unknown hazards and should be used with caution. Due to possible changes in Avient products and applicable national and international regulations and laws, the status of the products could change. Although certain hazards are described herein, Avient and



EVA 003.000% FE 3922 BEIGE

Page 22

Substance key: 000000781249	Revision Date: 09/21/2020
Version : 1 - 1 / CDN	Date of printing :01/24/2025

its subsidiaries and affiliates cannot guarantee that these are the only hazards that exist. This information is only valid for the current intended use, and is not valid for such Avient product used in conjunction with any other materials or in any process.

CA / EN