

Page 1

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

SECTION 1. IDENTIFICATION

Identification of the Avient Colorants Canada Inc.

company: 2 Lone Oak Court

Toronto, Ontario, M9C 5R9 Telephone No.: +1 514-832-2559

Information of the substance/preparation:

Product Stewardship

e-mail: SDS.NORAMMB@Clariant.com

Emergency tel. number: +1 CANUTEC (613) 996-6666

Trade name: ABS GP35 004.000% GREY

Material number: SB73653628

Synonyms: ABS GP35 004.000% GREY (SB73653628)

Chemical family: Colourant preparation

Carrier: ABS

Primary product use: Additive for plastic material processing

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Hazards Not Otherwise Classified:

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Colourant preparation

Carrier: ABS

Components

Chemical name	CAS-No.	Concentration (% w/w)
Crystalline silica, quartz	14808-60-7	0.1 - 1
C.I. Pigment Black 7	1333-86-4	0.1 - 1
Aluminium oxide	1344-28-1	0.1 - 1
Styrene	100-42-5	0.1 - 1
N,N'-Ethylenedi(stearamide)	110-30-5	1 - 5
C.I. Pigment Brown 24	68186-90-3	1 - 5
Limestone	1317-65-3	1 - 5



ABS GP35 004.000% GREY

Page 2

Substance key: 000000647311	Revision Date: 09/21/2020
Version: 1 - 1 / CDN	Date of printing :09/24/2021

C.I. Pigment White 6	13463-67-7	10 - 30
2-Propenenitrile, polymer with	9003-54-7	30 - 60
ethenylbenzene		30 - 00

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and by the Canadian WHMIS 2015 Hazardous Products Regulations (SOR/2015-17)., The hazardous ingredients of this product are encapsulated, therefore the material is not GHS classified for health and environmental hazards as exposure is not expected., Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

If inhaled : Move the victim to fresh air.

Give oxygen or artificial respiration if needed. Get immediate medical advice/ attention.

Never give anything by mouth to an unconscious person.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

In case of burns apply cold water until pain subsides then

seek medical advice.

Burns must be treated by a physician.

If molten polymer contact the skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burn. Skin absorption of

reground pellets is unlikely.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Get medical attention immediately if irritation develops and

persists.

If swallowed : Rinse mouth.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

Get medical advice/ attention.

Most important symptoms and effects, both acute and

delayed

The possible symptoms known are those derived from the

labelling (see section 2).

No additional symptoms are known.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet



Page 3

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Specific hazards during

firefighting

In case of fire hazardous decomposition products may be

produced such as:

Styrene

Hydrogen cyanide (hydrocyanic acid)

Acrylonitrile Carbon monoxide Carbon dioxide (CO2)

Take measures to prevent the build up of electrostatic charge.

Dust can form an explosive mixture in air.

Carbon oxides

Oxides of phosphorus

Metal oxides Sulphur oxides Styrene Hydrocarbons

Further information : Combustible material

In the event of fire and/or explosion do not breathe fumes. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Do not allow run-off from fire fighting to enter drains or water

courses.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Refer to protective measures listed in sections 7 and 8.

Avoid contact with skin, eyes and clothing.

Wash thoroughly after handling.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent product from entering drains.

Methods and materials for containment and cleaning up

Avoid dust formation.

Take measures to prevent the build up of electrostatic charge. Sweep up and shovel into suitable containers for disposal. Take up uncontaminated material and pass on for further

processing.

After cleaning, flush away traces with water.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : Take measures to prevent the build up of electrostatic charge.



ABS GP35 004.000% GREY

Page 4

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

fire and explosion

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice.

Use only with adequate ventilation/personal protection.

For personal protection see section 8. Avoid contact with skin, eyes and clothing. Use only with adequate ventilation.

When handling hot melts use suitable protective clothing. Avoid dust formation. Keep away from sources of ignition.

Lead off electrostatic charges.

Conditions for safe storage : Keep container tightly closed in a cool, well-ventilated place.

Protect from moisture.

Keep away from direct sunlight.

Further information on

storage conditions

Store in a cool, dry, well-ventilated area. Keep container

sealed when not in use.

Keep in an area equipped with sprinklers. Minimize dust generation and accumulation.

Materials to avoid : not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N,N'-Ethylenedi(stearamide)	110-30-5	TWA	10 mg/m3	CA AB OEL
		TWA	10 mg/m3	CA BC OEL
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
Crystalline silica, quartz	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
C.I. Pigment Brown 24	68186-90-3	TWÁ	0.5 mg/m3 (antimony)	CA AB OEL
		TWAEV	0.5 mg/m3	CA QC OEL



ABS GP35 004.000% GREY

Page 5

Substance key: 000000647311	Revision Date: 09/21/2020
Version: 1 - 1 / CDN	Date of printing :09/24/2021

			(antimony)	
		TWA	0.5 mg/m3	CA BC OEL
			(antimony)	
		TWA	0.5 mg/m3	ACGIH
			(antimony)	
C.I. Pigment Black 7	1333-86-4	TWA	3.5 mg/m3	CA AB OEL
		TWA	3 mg/m3	CA BC OEL
		(Inhalable)		
		TWAEV	3.5 mg/m3	CA QC OEL
		TWA	3 mg/m3	ACGIH
		(Inhalable		
		particulate		
		matter)		
Limestone	1317-65-3	TWA	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		(total dust)		
Aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		(total dust)	(Aluminium)	
		TWA	1 mg/m3	CA BC OEL
		(Respirable)	(Aluminium)	
		TWA	1 mg/m3	ACGIH
		(Respirable	(Aluminium)	
		particulate		
C. I. Diama ant White C	40400 07 7	matter)	40	
C.I. Pigment White 6	13463-67-7	TWA	10 mg/m3	CA AB OEL CA BC OEL
		TWA (Total	10 mg/m3	CA BC OEL
		dust) TWA	3 mg/m3	CA BC OEL
		(respirable	3 mg/ms	CA BC OEL
		dust fraction)		
		TWAEV	10 mg/m3	CA QC OEL
		(total dust)	10 1119/1113	OA QU OLL
Styrene	100-42-5	TWA	20 ppm	CA AB OEL
Otyrene	100 42 3	I VVA	85 mg/m3	ON ND OLL
		STEL	40 ppm	CA AB OEL
		0.22	170 mg/m3	ON THE SEE
		TWA	20 ppm	CA BC OEL
		STEL	40 ppm	CA BC OEL
		TWA	35 ppm	CA ON OEL
		STEL	100 ppm	CA ON OEL
		STEV	100 ppm	CA QC OEL
			426 mg/m3	530 022
		TWAEV	50 ppm	CA QC OEL
			213 mg/m3	
		TWA	20 ppm	ACGIH
		STEL	40 ppm	ACGIH

Engineering measures

Use only in area provided with appropriate exhaust ventilation.

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Use engineering controls such as local or general exhaust to



ABS GP35 004.000% GREY

Page 6

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

maintain airborne concentrations below exposure limits.

Personal protective equipment

Respiratory protection : Use NIOSH/MSHA approved respirators following

manufacturer's recommendations where dust or fume may be

generated.

Use respiratory protective equipment when using this product

at elevated temperatures (see section 8).

Hand protection

Remarks : Nitrile rubber gloves. Impervious butyl rubber gloves PVC

Neoprene gloves When handling hot material, use heat

resistant gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : Wear protective clothing, including long sleeves and gloves,

to prevent skin contact.

When handling hot melts use suitable protective clothing.

Hygiene measures : The usual Industrial Hygiene precautions must be taken

during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during

work intervals and after work.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Granules

Colour : grey

Odour : characteristic

Odour Threshold : Not applicable

pH : Not applicable

Melting point : > 90 °C

Boiling point : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : not determined

Self-ignition : Not applicable



Page 7

ABS GP35 004.000% GREY

Substance key: 000000647311 Revision Date: 09/21/2020 Version: 1-1/CDN Date of printing :09/24/2021

Upper explosion limit / upper

flammability limit

: not tested.

Lower explosion limit / Lower : not tested.

flammability limit

Vapour pressure Not applicable

Relative vapour density Not applicable

Relative density not available

not tested. Density

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

This property is not applicable for mixtures.

Decomposition temperature To the best of our current knowledge, no thermal

decomposition of the product is expected if it is processed

according to good manufacturing practices. See section 10.4. "Conditions to avoid"

Viscosity

Viscosity, dynamic Not applicable

Viscosity, kinematic Not applicable

Explosive properties no data available

no data available

Oxidizing properties : not available

Surface tension Not relevant

Particle size Product specific

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability Stable

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid To avoid thermal decomposition, do not overheat.

Heating can release hazardous gases.

Keep away from heat, sparks, open flames, and other sources



Page 8

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

of ignition.

If small particles are generated during further processing, handling or by other means, may form combustible dust

concentrations in air.

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Keep away from heat and sources of ignition.

Strong oxidizing agents

Strong bases

Incompatible materials : no data available

See under section "Conditions to avoid"

Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed Carbon oxides

Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

None known.

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Crystalline silica, quartz:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : Remarks: no data available

C.I. Pigment Black 7:

Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg

Method: OECD Test Guideline 401

GLP: no

Remarks: No significant adverse effects were reported

Acute inhalation toxicity : LC0 (Rat): > 0.0046 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403 GLP: No information available.

Assessment: The substance or mixture has no acute

inhalation toxicity



Page 9

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Acute dermal toxicity : Remarks: not required

Styrene:

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

N,N'-Ethylenedi(stearamide):

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 6.3 mg/l

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

C.I. Pigment Brown 24:

Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg

Method: BASF test

GLP: no

Acute inhalation toxicity : Remarks: Not applicable

Acute dermal toxicity : Remarks: Not applicable

C.I. Pigment White 6:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg

Method: OECD Test Guideline 425

GLP: no

Acute inhalation toxicity : LC50 (Rat, male and female): 3.4 - 5.1 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: no

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: not required



ABS GP35 004.000% GREY

Page 10

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

Crystalline silica, quartz:

Remarks: no data available

C.I. Pigment Black 7:

Species: Rabbit

Exposure time: 4 - 24 h

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: no

Styrene:

Result: Irritating to skin.

N,N'-Ethylenedi(stearamide):

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

C.I. Pigment Brown 24:

Species: Rabbit Exposure time: 24 h Method: Draize Test Result: No skin irritation

GLP: no

C.I. Pigment White 6:

Species: Rabbit Exposure time: 4 h

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: no

Serious eye damage/eye irritation

Product:

Result: No eye irritation

Components:

Crystalline silica, quartz:

Remarks: no data available



ABS GP35 004.000% GREY

Page 11

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

C.I. Pigment Black 7:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: no

Styrene:

Result: Irritating to eyes.

N,N'-Ethylenedi(stearamide):

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

C.I. Pigment Brown 24:

Species: rabbit eye Result: slight irritation Method: FDA guideline

GLP: no

C.I. Pigment White 6:

Species: rabbit eye Result: No eye irritation

Method: OECD Test Guideline 405 GLP: No information available.

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

Crystalline silica, quartz:

Remarks: no data available

C.I. Pigment Black 7:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406 Result: Not a skin sensitizer.

GLP: yes

Styrene:

Result: Does not cause skin sensitisation.



Page 12

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

N,N'-Ethylenedi(stearamide):

Species: Mouse

Method: OECD Test Guideline 429 Result: Not a skin sensitizer.

C.I. Pigment Brown 24:

Remarks: Not applicable

C.I. Pigment White 6:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Dermal

Species: Mouse

Method: OECD Test Guideline 429 Result: Not a skin sensitizer. GLP: No information available.

Test Type: Buehler Test Exposure routes: Dermal Species: Guinea pig

Method: OECD Test Guideline 406 Result: Not a skin sensitizer.

GLP: yes

Test Type: Respiratory system

Exposure routes: inhalation (dust/mist/fume)

Species: Mouse Method: Other

Result: Does not cause respiratory sensitisation.

GLP: No information available.

Germ cell mutagenicity

Components:

C.I. Pigment Black 7:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test Type: In vitro gene mutation study in mammalian cells

Test system: Rodent cell line Metabolic activation: without Method: OECD Test Guideline 476

Result: positive

GLP: No information available.

Test Type: Micronucleus test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation



Page 13

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Method: OECD Test Guideline 487

Result: negative GLP: yes

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Styrene:

Genotoxicity in vitro : Remarks: no data available

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

N,N'-Ethylenedi(stearamide):

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: Mammalian cell gene mutation assay

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Germ cell mutagenicity -

Assessment

In vitro tests did not show mutagenic effects

C.I. Pigment Brown 24:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium Concentration: 100 - 5000 µg/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test Type: Ames test

Test system: Escherichia coli Concentration: 2,5 - 5000 µg/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes



Page 14

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster lung cells

Concentration: 0,5 - 900 µg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative GLP: yes

Test Type: In vitro gene mutation study in mammalian cells

Test system: mouse lymphoma cells Concentration: 3,13 - 100 µg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

GLP: yes

Germ cell mutagenicity -

Assessment

It is concluded that the product is not mutagenic based on

evaluation of several mutagenicity tests.

C.I. Pigment White 6:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium Concentration: 333 - 5000 µg/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative GLP: yes

Test Type: Ames test

Test system: Escherichia coli Concentration: 333 - 5000 µg/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative GLP: yes

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Strain: ICR

Cell type: Erythrocytes

Application Route: oral (gavage)
Exposure time: single treatment
Dose: 500 - 1000 - 2000 mg/kg
Method: OECD Test Guideline 474

Result: negative

GLP: yes

Germ cell mutagenicity -

Assessment

In vitro tests did not show mutagenic effects, In vivo tests did

not show mutagenic effects



Page 15

ABS GP35 004.000% GREY

Substance key: 000000647311 Revision Date: 09/21/2020 Version: 1-1/CDN Date of printing :09/24/2021

Carcinogenicity

Components:

C.I. Pigment Black 7:

Remarks: Carbon Black should not be classified for carcinogenicity according to the criteria of the Globally Harmonized System of Classification and Labelling of Chemicals. Human health studies show that exposure to carbon black does not increase the risk of carcinogenicity. Studies in laboratory animals show that lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rat tumors are a result of a secondary non-genotoxic mechanism associated with the phenomenon of lung overload. This is a species-specific mechanism that has questionable relevance for classification in humans. Thus a carcinogenicity classification for Carbon Black is not warranted.

Carcinogenicity -

: Not classifiable as a human carcinogen.

Assessment

Styrene:

Carcinogenicity -

: Not classifiable as a human carcinogen.

Assessment

N,N'-Ethylenedi(stearamide):

Carcinogenicity -

No information available.

Assessment

C.I. Pigment Brown 24:

Carcinogenicity -

Assessment

: Not classifiable as a human carcinogen.

C.I. Pigment White 6:

Carcinogenicity -Assessment

: Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

C.I. Pigment Black 7:

Effects on foetal Test Type: Pre-natal

Species: Rabbit, male and female development

Strain: New Zealand white Application Route: Inhalation Dose: 10% diesel exhaust emission Duration of Single Treatment: 12 d Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

GLP: no

Remarks: By analogy with a product of similar composition

Reproductive toxicity -

No evidence of adverse effects on sexual function and fertility,

Assessment or on development, based on animal experiments.



Page 16

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Styrene:

Effects on fertility : Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity -

Assessment

Suspected human reproductive toxicant

N,N'-Ethylenedi(stearamide):

Effects on foetal : Test Type: Pre-natal

development Species: Rat

Strain: Sprague-Dawley

Application Route: oral (gavage)

General Toxicity Maternal: NOAEL: >= 1,000 mg/kg body

weight

Method: OECD Test Guideline 414

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

C.I. Pigment Brown 24:

Effects on fertility : Test Type: One generation study

Species: Rat, male and female

Strain: Sprague-Dawley

Application Route: oral (gavage) Dose: 250 - 500 - 1000 mg/kg

General Toxicity - Parent: NOAEL: >= 1,000 mg/kg body

weiaht

General Toxicity F1: NOAEL: >= 1,000 mg/kg body weight

Method: OECD Test Guideline 422

GLP: yes

Effects on foetal : Species: Rat

development Strain: Sprague-Dawley

Application Route: oral (gavage) Dose: 250 - 500 - 1000 mg/kg

General Toxicity Maternal: NOAEL: >= 1,000 mg/kg body

weight

Teratogenicity: NOAEL: >= 1,000 mg/kg body weight

Method: OECD Test Guideline 422

GLP: yes

Reproductive toxicity -

Assessment

No reproductive toxicity to be expected. No teratogenic effects to be expected.

C.I. Pigment White 6:

Effects on fertility : Remarks: no data available

Effects on foetal : Test Type: Pre-natal development : Species: Rat, female

Strain: wistar



ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Application Route: oral (gavage) Dose: 100, 300, 1000 mg/kg bw Duration of Single Treatment: 14 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight Developmental Toxicity: NOAEL: 1,000 mg/kg body weight Embryo-foetal toxicity: NOEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Remarks: No significant adverse effects were reported

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments. Did not show teratogenic effects in animal experiments.

STOT - single exposure

Components:

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Styrene:

Assessment: May cause respiratory irritation.

N,N'-Ethylenedi(stearamide):

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

C.I. Pigment Brown 24:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Styrene:

Target Organs: hearing organs

Assessment: Causes damage to organs through prolonged or repeated exposure.

Page 17



Page 18

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

N,N'-Ethylenedi(stearamide):

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

C.I. Pigment Brown 24:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

C.I. Pigment Black 7:

Species: Rat, female NOAEL: 52 mg/kg bw/day Application Route: oral (feed) Exposure time: 1 a - 2 a Number of exposures: daily Dose: 2,05 g/kg of chow diet

Group: yes Method: Other

GLP: No information available.

Remarks: No adverse effect has been observed in chronic toxicity tests.

Species: Rat, male NOAEL: 0.0011 mg/l LOAEL: 0.0071 mg/l Application Route: Inhalation Test atmosphere: dust/mist

Exposure time: 13 w Number of exposures: 6 h per day; 5 d per week

Dose: 1,1 - 7,1 - 52,8 mg/m3

Group: yes Method: Other

GLP: No information available.

Species: Mouse, male and female Application Route: Skin contact

Exposure time: 12-18 m

Number of exposures: 3 times per week Dose: 20% carbon black suspensions

Group: yes Method: Other GLP: no

Remarks: No adverse effect has been observed in chronic toxicity tests.

Styrene:

Remarks: This information is not available.



ABS GP35 004.000% GREY

Page 19

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

N,N'-Ethylenedi(stearamide):

Species: Rat, male and female NOEL: >= 1000 mg/kg bw/day Application Route: oral (gavage) Method: OECD Test Guideline 408

C.I. Pigment Brown 24:

Species: Rat, male and female

NOAEL: 500 mg/kg

Application Route: oral (feed)

Exposure time: 90 d Number of exposures: daily

Dose: 0,5 - 5 - 50 - 500 mg/kg

Group: yes

Method: OECD Test Guideline 408 GLP: No information available.

Application Route: Inhalation

Remarks: not tested.

Application Route: Skin contact

Remarks: not tested.

C.I. Pigment White 6:

Species: Rat, male

NOEL: > 24000 mg/kg bw/day Application Route: oral (gavage)

Exposure time: 29 d

Number of exposures: daily

Dose: 24000 mg/kg

Group: yes

Method: OECD Test Guideline 407 GLP: No information available.

Species: Rat, male and female

NOAEL: 0.01 mg/l

Application Route: Inhalation

Exposure time: 2 a

Number of exposures: 6 hours/day, 5 days/week

Dose: 0,0106 - 0,0507 - 0,250 mg/l

Group: yes

Method: Repeated Dose Toxicity (chronic Toxicity)

GLP: no

Aspiration toxicity

Components:

C.I. Pigment Black 7:

No aspiration toxicity classification



Page 20

ABS GP35 004.000% GREY

Substance key: 000000647311 Revision Date: 09/21/2020 Version: 1-1/CDN Date of printing :09/24/2021

Styrene:

May be fatal if swallowed and enters airways.

N,N'-Ethylenedi(stearamide):

no data available

C.I. Pigment Brown 24:

No aspiration toxicity classification

C.I. Pigment White 6:

No aspiration toxicity classification

Experience with human exposure

Product:

General Information The possible symptoms known are those derived from the

labelling (see section 2).

Further information

Components:

C.I. Pigment White 6:

Remarks: Lung damage possible.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: no data available

Components:

Crystalline silica, quartz:

Toxicity to fish : Remarks: no data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: no data available

Toxicity to algae/aquatic

plants

Remarks: no data available

Toxicity to fish (Chronic

toxicity)

Remarks: no data available

Toxicity to daphnia and other : Remarks: no data available

aquatic invertebrates (Chronic toxicity)



Page 21

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

C.I. Pigment Black 7:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l

End point: mortality Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no

Method: OECD Test Guideline 203

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 5,600 mg/l

End point: Immobilization Exposure time: 24 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 202

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 201

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to fish (Chronic

toxicity)

Remarks: not required

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

Remarks: not required

Toxicity to microorganisms : EC0 (activated sludge): > 400 mg/l

End point: Bacteria toxicity (growth inhibition)

Exposure time: 3 h Test Type: static test Method: DIN 38412

GLP: no

Toxicity to soil dwelling

organisms

Test Type: Other

Method: Other

GLP: No information available.

Remarks: This product does not have any known adverse

effect on the soil organisms tested.



Page 22

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Styrene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.02 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.7 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 4.9

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

Remarks: no data available

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

Remarks: no data available

Toxicity to microorganisms : EC50 (Bacteria): 500 mg/l

Exposure time: 0.5 h

Toxicity to soil dwelling

organisms

Remarks: Not applicable

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial

organisms

Remarks: Not applicable

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

N,N'-Ethylenedi(stearamide):

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 0.027 mg/l

End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.0022 mg/l

Exposure time: 48 h Test Type: semi-static test

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (algae)): 0.053 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility



Page 23

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Toxicity to fish (Chronic

toxicity)

Remarks: no data available

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC50 (Daphnia magna (Water flea)): 0.0056 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: No toxicity at the limit of solubility

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h Test Type: static test

Method: OECD Test Guideline 209

Toxicity to soil dwelling

organisms

NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg

Exposure time: 56 d

Method: OECD Test Guideline 222

Sediment toxicity : NOEC: >= 1000 mg/kg dry weight (d.w.)

Test Type: static test Sediment: Artificial sediment Exposure duration: 28 d

Method: OECD Test Guideline 218

C.I. Pigment Brown 24:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l

Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: DIN 38412 T.15

GLP: no

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 202

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 201

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to fish (Chronic : Remarks: not required



Page 24

ABS GP35 004.000% GREY

Substance key: 000000647311 Revision Date: 09/21/2020 Version: 1-1/CDN Date of printing :09/24/2021

toxicity)

Toxicity to daphnia and other : Remarks: not required

aquatic invertebrates (Chronic toxicity)

Toxicity to microorganisms EC50 (Pseudomonas putida): > 10,000 mg/l

End point: Bacteria toxicity (respiration inhibition)

Exposure time: 0.5 h Test Type: aquatic Analytical monitoring: no Method: DIN 38412 T.27

GLP: no

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to soil dwelling

organisms

Remarks: Not applicable

Plant toxicity Remarks: Not applicable

Sediment toxicity Remarks: Not applicable

Toxicity to terrestrial

organisms

Remarks: Not applicable

C.I. Pigment White 6:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

> Exposure time: 96 h Test Type: static test Analytical monitoring: no

Method: EPA GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 203 GLP: No information available.

Remarks: The details of the toxic effect relate to the nominal

concentration.

LC50 (Cyprinodon variegatus (sheepshead minnow)): >

10,000 mg/l

Exposure time: 96 h Test Type: semi-static test

Analytical monitoring: no data available Method: OECD Test Guideline 203

GLP: yes

Remarks: The details of the toxic effect relate to the nominal



Page 25

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

concentration.

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Analytical monitoring: no data available Method: OECD Test Guideline 202

GLP: no data available

Remarks: The details of the toxic effect relate to the nominal

concentration.

LC50 (Acartia tonsa): > 10,000 mg/l

Exposure time: 48 h

Analytical monitoring: no data available Method: ISO 14669 and PARCOM method

GLP: ves

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (microalgae)): 61 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no

Method: EPA

GLP: No information available.

Remarks: The details of the toxic effect relate to the nominal

concentration.

EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l

End point: Growth rate Exposure time: 72 h

Analytical monitoring: no data available

Method: ISO 10253

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to fish (Chronic

toxicity)

LC50 (Oncorhynchus mykiss (rainbow trout)): 7.31 mg/l

Exposure time: 28 d Test Type: static test Analytical monitoring: yes

Method: Other

GLP: No information available.

Remarks: By analogy with a product of similar composition

Toxicity to microorganisms

EC50 (activated sludge of a predominantly domestic sewage):

> 1,000 mg/l

End point: Bacteria toxicity (respiration inhibition)

Exposure time: 3 h Test Type: aquatic

Method: OECD Test Guideline 209

GLP: yes

Remarks: The details of the toxic effect relate to the nominal



Page 26

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

concentration.

NOEC (activated sludge of a predominantly domestic

sewage): >= 1,000 mg/l

End point: Bacteria toxicity (respiration inhibition)

Exposure time: 3 h Test Type: aquatic

Method: OECD Test Guideline 209

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to soil dwelling

organisms

Test Type: artificial soil

NOEC (Folsomia candida): 0,1 ->= 10 %

Exposure time: 28 d End point: mortality Method: ISO 11267

GLP: no

Remarks: By analogy with a product of similar composition This product does not have any known adverse effect on the

soil organisms tested.

Plant toxicity : NOEC: >= 10 %

Exposure time: 20 h End point: Growth

Species: Lactuca sativa (lettuce) Analytical monitoring: yes

Method: Other GLP: no

Remarks: By analogy with a product of similar composition

No effect on the growth was observed.

Sediment toxicity : NOEC (Hyalella azteca (Scud)): >= 100000 %

Analytical monitoring: no Sediment: artificial soil Exposure duration: 28 d Nominal / Measured: nominal Basis for effect: mortality

Method: Other GLP: no

Remarks: By analogy with a product of similar composition

NOEC: >= 14989 mg/kg dry weight (d.w.) Analytical monitoring: no data available

Sediment: Natural sediment Exposure duration: 10 d Nominal / Measured: nominal Basis for effect: mortality

Method: Other GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.



Page 27

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

Persistence and degradability

Components:

C.I. Pigment Black 7:

Biodegradability : Remarks: Not applicable

Styrene:

Biodegradability : aerobic

Result: Readily biodegradable. Biodegradation: 70.9 % Exposure time: 28 d

N,N'-Ethylenedi(stearamide):

Biodegradability : aerobic

Inoculum: activated sludge Carbon dioxide (CO2)

Result: Not readily biodegradable.

Biodegradation: 5.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

C.I. Pigment Brown 24:

Biodegradability : Remarks: Not applicable for inorganic compound.

Physico-chemical

removability

Remarks: Inorganic product, cannot be eliminated from the

water by biological purification processes.

C.I. Pigment White 6:

Biodegradability : Remarks: Not applicable for inorganic compound.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: not tested.

Components:

Crystalline silica, quartz:

Bioaccumulation : Remarks: no data available

C.I. Pigment Black 7:

Bioaccumulation : Remarks: Not applicable

Styrene:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water,

accumulation in organisms is not expected.



Page 28

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

N,N'-Ethylenedi(stearamide):

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

Remarks: Not applicable

C.I. Pigment Brown 24:

Bioaccumulation : Remarks: Not relevant for inorganic substances

C.I. Pigment White 6:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 20 - 200

Exposure time: 14 d Concentration: 0.1 - 1 mg/l

Method: Other

GLP: No information available.

Remarks: Does not accumulate in organisms.

Partition coefficient: n-

octanol/water

Remarks: inorganic

Mobility in soil

Product:

Distribution among environmental compartments

Remarks: not tested.

Components:

C.I. Pigment Black 7:

Distribution among : Adsorption/Soil environmental compartments : Medium: water - soil

Remarks: Not applicable

Styrene:

Distribution among

environmental compartments

Remarks: no data available

N,N'-Ethylenedi(stearamide):

Distribution among : log Koc: 8.6 - 8.91 environmental compartments Method: calculated

C.I. Pigment Brown 24:

Distribution among : Remarks: Not applicable

environmental compartments

C.I. Pigment White 6:

Mobility : Remarks: Adsorption to solid soil phase is possible.



Page 29

ABS GP35 004.000% GREY

Substance key: 000000647311 Revision Date: 09/21/2020

Version: 1 - 1 / CDN Date of printing:09/24/2021

Distribution among environmental compartments

Adsorption/Soil Medium: water - soil

log Koc: 4.61 Method: Other

Other adverse effects

Product:

Results of PBT and vPvB

assessment

Remarks: No information is available as no chemical safety

report (CSR) is required.

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

Components:

C.I. Pigment Black 7:

Environmental fate and

pathways

not available

Results of PBT and vPvB

assessment

The substance is not identified as a PBT or as a vPvB

substance.

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

Styrene:

Environmental fate and

pathways

no data available

Results of PBT and vPvB

assessment

This substance is not considered to be persistent,

bioaccumulating and toxic (PBT).

Additional ecological

information

The product should not be allowed to enter drains, water

courses or the soil.

N,N'-Ethylenedi(stearamide):

Results of PBT and vPvB

assessment

The substance is not identified as a PBT or as a vPvB

substance.

C.I. Pigment Brown 24:

Environmental fate and

pathways

not available

Results of PBT and vPvB

assessment

The substance is inorganic, thus a PBT and vPvB criteria

assessment is not applicable according to Annex XIII of

Regulation (EC) 1907/2006.

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.



Page 30

ABS GP35 004.000% GREY

Substance key: 000000647311 Revision Date: 09/21/2020

Version: 1 - 1 / CDN Date of printing:09/24/2021

C.I. Pigment White 6:

Environmental fate and

pathways

: not available

Results of PBT and vPvB

assessment

This substance is not considered to be persistent,

bioaccumulating and toxic (PBT).

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of this product in accordance with all applicable local,

state and federal regulations.

Contaminated packaging : Regulations concerning reuse or disposal of used packaging

materials must be observed.

SECTION 14. TRANSPORT INFORMATION

TDG not restricted
IATA not restricted
IMDG not restricted

SECTION 15. REGULATORY INFORMATION

NPRI Components : Chromium (III) compound

Antimony compounds

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)



Page 31

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and

safety, Schedule 1, Part 1: Permissible exposure values for

airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA ON OEL / STEL : Short-Term Exposure Limit (STEL)
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 09/21/2020 Date format : mm/dd/yyyy



Page 32

ABS GP35 004.000% GREY

 Substance key: 000000647311
 Revision Date: 09/21/2020

 Version: 1 - 1 / CDN
 Date of printing: 09/24/2021

The information contain herein is accurate to the best knowledge of Avient Corporation and its subsidiaries and affiliates. However, neither Avient nor any of its subsidiaries or affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of the Avient product is the sole responsibility of the user. Any material may present unknown hazards and should be used with caution. Due to possible changes in Avient products and applicable national and international regulations and laws, the status of the products could change. Although certain hazards are described herein, Avient and its subsidiaries and affiliates cannot guarantee that these are the only hazards that exist. This information is only valid for the current intended use, and is not valid for such Avient product used in conjunction with any other materials or in any process.

CA / EN