

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 1

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

SECTION 1. IDENTIFICATION

Identification of the company:

Avient Colorants Canada Inc.
2 Lone Oak Court
Toronto, Ontario, M9C 5R9
Telephone No.: +1 514-832-2559

Information of the substance/preparation:

Product Stewardship
e-mail: SDS.NORAMMB@avient.com

Emergency tel. number: +1 CANUTEC (613) 996-6666

Trade name:

EVA 003.000% DC 17W1

Material number:

PR73754422

Chemical family:

Colourant preparation
Carrier: crosslinked PE

Primary product use:

Additive for plastic material processing

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Hazards Not Otherwise Classified:

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Colourant preparation
Carrier: crosslinked PE

Components

Chemical name	CAS-No.	Concentration (% w/w)
C.I. Pigment Black 7	1333-86-4	0.1 - 1
Aluminium oxide	1344-28-1	0.1 - 1
Amorphous silicon dioxide	7631-86-9	0.1 - 1
Calcium carbonate	471-34-1	0.1 - 1
Vinyl acetate	108-05-4	0.1 - 1
C.I. Pigment Yellow 53	8007-18-9	5 - 10
C.I. Pigment White 6	13463-67-7	30 - 60

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 2

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and by the Canadian WHMIS 2015 Hazardous Products Regulations (SOR/2015-17)., The hazardous ingredients of this product are encapsulated, therefore the material is not GHS classified for health and environmental hazards as exposure is not expected., Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|---|
| If inhaled | : | Move the victim to fresh air.
Give oxygen or artificial respiration if needed.
Get immediate medical advice/ attention.
Never give anything by mouth to an unconscious person. |
| In case of skin contact | : | Wash off immediately with plenty of water for at least 15 minutes.
In case of burns apply cold water until pain subsides then seek medical advice.
Burns must be treated by a physician.
If molten polymer contact the skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burn. Skin absorption of reground pellets is unlikely. |
| In case of eye contact | : | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Get medical attention immediately if irritation develops and persists. |
| If swallowed | : | Rinse mouth.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
Get medical advice/ attention. |
| Most important symptoms and effects, both acute and delayed | : | The possible symptoms known are those derived from the labelling (see section 2).
No additional symptoms are known. |
| Notes to physician | : | Treat symptomatically. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|--------------------------------------|---|---|
| Suitable extinguishing media | : | Water spray
Foam
Carbon dioxide (CO2)
Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during firefighting | : | In case of fire hazardous decomposition products may be produced such as: |

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 3

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Carbon monoxide
Carbon dioxide (CO₂)
Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Sulphur oxides
Metal oxides

- Further information : Combustible material
In the event of fire and/or explosion do not breathe fumes.
During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion
Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Do not allow run-off from fire fighting to enter drains or water courses.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
Avoid contact with skin, eyes and clothing.
Wash thoroughly after handling.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent product from entering drains.
- Methods and materials for containment and cleaning up : Avoid dust formation.
Take measures to prevent the build up of electrostatic charge.
Sweep up and shovel into suitable containers for disposal.
Take up uncontaminated material and pass on for further processing.
After cleaning, flush away traces with water.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take measures to prevent the build up of electrostatic charge.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Use only with adequate ventilation/personal protection.
For personal protection see section 8.
Avoid contact with skin, eyes and clothing.
Use only with adequate ventilation.
When handling hot melts use suitable protective clothing.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 4

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Avoid dust formation. Keep away from sources of ignition.
Lead off electrostatic charges.

Conditions for safe storage : Keep container tightly closed in a cool, well-ventilated place.
Protect from moisture.
Keep away from direct sunlight.

Further information on storage conditions : Store in a cool, dry, well-ventilated area. Keep container sealed when not in use.
Keep in an area equipped with sprinklers.
Minimize dust generation and accumulation.

Materials to avoid : not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
C.I. Pigment Yellow 53	8007-18-9	TWA	0.5 mg/m3 (antimony)	CA AB OEL
		TWAEV	0.5 mg/m3 (antimony)	CA QC OEL
		TWA	0.5 mg/m3 (antimony)	CA BC OEL
		TWA	0.5 mg/m3 (antimony)	ACGIH
C.I. Pigment Black 7	1333-86-4	TWA	3.5 mg/m3	CA AB OEL
		TWA (Inhalable)	3 mg/m3	CA BC OEL
		TWAEV	3.5 mg/m3	CA QC OEL
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
C.I. Pigment White 6	13463-67-7	TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
Aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
		TWAEV (total dust)	10 mg/m3 (Aluminium)	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	CA BC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	ACGIH

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 5

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

		particulate matter)		
Amorphous silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
Calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m3	CA QC OEL
Vinyl acetate	108-05-4	TWA	10 ppm 35 mg/m3	CA AB OEL
		STEL	15 ppm 53 mg/m3	CA AB OEL
		TWA	10 ppm	CA BC OEL
		STEL	15 ppm	CA BC OEL
		TWAEV	10 ppm 35 mg/m3	CA QC OEL
		STEV	15 ppm 53 mg/m3	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH

Engineering measures : Use only in area provided with appropriate exhaust ventilation.
Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.
Use engineering controls such as local or general exhaust to maintain airborne concentrations below exposure limits.

Personal protective equipment

Respiratory protection : Use NIOSH/MSHA approved respirators following manufacturer's recommendations where dust or fume may be generated.
Use respiratory protective equipment when using this product at elevated temperatures (see section 8).

Hand protection
Remarks : Nitrile rubber gloves. Impervious butyl rubber gloves PVC Neoprene gloves When handling hot material, use heat resistant gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : Wear protective clothing, including long sleeves and gloves, to prevent skin contact.
When handling hot melts use suitable protective clothing.

Hygiene measures : The usual Industrial Hygiene precautions must be taken during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during work intervals and after work.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 6

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Granules
Colour	: grey
Odour	: characteristic
Odour Threshold	: Not applicable
pH	: Not applicable
Melting point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: not determined
Self-ignition	: Not applicable
Upper explosion limit / upper flammability limit	: not tested.
Lower explosion limit / Lower flammability limit	: not tested.
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Relative density	: not available
Density	: not tested.
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: This property is not applicable for mixtures.
Decomposition temperature	: To the best of our current knowledge, no thermal decomposition of the product is expected if it is processed according to good manufacturing practices. See section 10.4. "Conditions to avoid"

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 7

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Viscosity	
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable
Explosive properties	: no data available no data available
Oxidizing properties	: not available
Surface tension	: Not relevant
Particle size	: Product specific

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Heating can release hazardous gases. Keep away from heat, sparks, open flames, and other sources of ignition. If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Incompatible materials	: none Strong oxidizing agents Halogenated hydrocarbons
Hazardous decomposition products	: No hazardous decomposition products if stored and handled as prescribed

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

None known.

Acute toxicity

Product:

Acute inhalation toxicity	: Acute toxicity estimate: 12.8 mg/l Exposure time: 4 h
---------------------------	--

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 8

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Test atmosphere: dust/mist
Method: Calculation method

Components:

C.I. Pigment Black 7:

- Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg
Method: OECD Test Guideline 401
GLP: no
Remarks: No significant adverse effects were reported
- Acute inhalation toxicity : LC0 (Rat): > 0.0046 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: No information available.
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Remarks: not required

Aluminium oxide:

- Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg
Method: OECD Test Guideline 401
GLP: No information available.
- Acute inhalation toxicity : LC50 (Rat, male and female): > 2.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Remarks: Not applicable

Amorphous silicon dioxide:

- Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Remarks: No significant adverse effects were reported
- Acute inhalation toxicity : LC50 (Rat, male and female): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: Other

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 9

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

GLP: no

Vinyl acetate:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

C.I. Pigment White 6:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 425
GLP: no

Acute inhalation toxicity : LC50 (Rat, male and female): 3.4 - 5.1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: no
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity
Remarks: not required

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

C.I. Pigment Black 7:

Species: Rabbit
Exposure time: 4 - 24 h
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: no

Aluminium oxide:

Species: Rabbit
Exposure time: 24 h
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: No information available.

Amorphous silicon dioxide:

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 10

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

C.I. Pigment White 6:

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: no

Serious eye damage/eye irritation

Product:

Result: No eye irritation

Components:

C.I. Pigment Black 7:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: no

Aluminium oxide:

Result: Mild eye irritation

Amorphous silicon dioxide:

Species: Rabbit
Result: No eye irritation
Exposure time: 24 h
Method: OECD Test Guideline 405
GLP: yes

C.I. Pigment White 6:

Species: rabbit eye
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: No information available.

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

C.I. Pigment Black 7:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Not a skin sensitizer.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 11

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

GLP: yes

Aluminium oxide:

Test Type: Draize Test
Exposure routes: Dermal
Species: Guinea pig
Method: Draize Test
Result: Not a skin sensitizer.
GLP: no

Test Type: Respiratory system
Exposure routes: inhalation (dust/mist/fume)
Species: Mouse
Method: Other
Result: Not a skin sensitizer.
GLP: no

Amorphous silicon dioxide:

Remarks: no data available

C.I. Pigment White 6:

Test Type: Local lymph node assay (LLNA)
Exposure routes: Dermal
Species: Mouse
Method: OECD Test Guideline 429
Result: Not a skin sensitizer.
GLP: No information available.

Test Type: Buehler Test
Exposure routes: Dermal
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Not a skin sensitizer.
GLP: yes

Test Type: Respiratory system
Exposure routes: inhalation (dust/mist/fume)
Species: Mouse
Method: Other
Result: Does not cause respiratory sensitisation.
GLP: No information available.

Germ cell mutagenicity

Components:

C.I. Pigment Black 7:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 12

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

GLP: yes

Test Type: In vitro gene mutation study in mammalian cells
Test system: Rodent cell line
Metabolic activation: without
Method: OECD Test Guideline 476
Result: positive
GLP: No information available.

Test Type: Micronucleus test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Aluminium oxide:

Genotoxicity in vitro : Test Type: In vitro gene mutation study in mammalian cells
Test system: mouse lymphoma cells
Concentration: 6,1 - 780 µg/ml
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes
Remarks: By analogy with a product of similar composition

Genotoxicity in vivo : Test Type: Chromosome Aberration Test
Species: Rat (female)
Strain: wistar
Cell type: Bone marrow
Application Route: oral (gavage)
Exposure time: Single exposure
Dose: 500 - 1000 - 2000 mg/kg
Method: OECD Test Guideline 475
Result: positive
GLP: No information available.

Test Type: Micronucleus test
Species: Rat (female)
Strain: wistar
Cell type: Bone marrow
Application Route: oral (gavage)
Exposure time: Single exposure
Dose: 500 - 1000 - 2000 mg/kg
Method: OECD Test Guideline 474
Result: positive
GLP: No information available.

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 13

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Amorphous silicon dioxide:

Genotoxicity in vitro

: Test Type: Ames test
Test system: Salmonella typhimurium
Concentration: 667 - 10000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: In vitro gene mutation study in mammalian cells
Test system: Chinese hamster ovary cells
Concentration: 10 - 500 µg/ml
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Concentration: 38 - 1000 µg/ml
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Genotoxicity in vivo

: Test Type: Cytogenetic assay
Species: Rat (male)
Strain: Fischer F344
Application Route: Inhalation
Exposure time: 13 w, 6 h/d, 5 d/wk
Dose: ca. 50 mg/m³
Method: Other
Result: negative
GLP: No information available.

Germ cell mutagenicity -
Assessment

: In vitro tests did not show mutagenic effects, In vivo tests did not show mutagenic effects

C.I. Pigment White 6:

Genotoxicity in vitro

: Test Type: Ames test
Test system: Salmonella typhimurium
Concentration: 333 - 5000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Ames test
Test system: Escherichia coli
Concentration: 333 - 5000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 14

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (male and female)
Strain: ICR
Cell type: Erythrocytes
Application Route: oral (gavage)
Exposure time: single treatment
Dose: 500 - 1000 - 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : In vitro tests did not show mutagenic effects, In vivo tests did not show mutagenic effects

Carcinogenicity

Components:

C.I. Pigment Black 7:

Remarks: Carbon Black should not be classified for carcinogenicity according to the criteria of the Globally Harmonized System of Classification and Labelling of Chemicals. Human health studies show that exposure to carbon black does not increase the risk of carcinogenicity. Studies in laboratory animals show that lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rat tumors are a result of a secondary non-genotoxic mechanism associated with the phenomenon of lung overload. This is a species-specific mechanism that has questionable relevance for classification in humans. Thus a carcinogenicity classification for Carbon Black is not warranted.

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Aluminium oxide:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

Amorphous silicon dioxide:

Species: Rat, (male and female)
Application Route: oral (feed)
Exposure time: 103 w
Dose: 1,25 - 2,5 - 5 % in diet
Group: yes
Frequency of Treatment: daily
NOAEL: ca. 1,800 - 3,000 mg/kg bw/day
Method: OECD Test Guideline 453
Result: negative
GLP: No information available.

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 15

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Vinyl acetate:

Carcinogenicity - Assessment : Suspected human carcinogens

C.I. Pigment White 6:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

C.I. Pigment Black 7:

Effects on foetal development : Test Type: Pre-natal
Species: Rabbit, male and female
Strain: New Zealand white
Application Route: Inhalation
Dose: 10% diesel exhaust emission
Duration of Single Treatment: 12 d
Method: OECD Test Guideline 414
Result: No effects on fertility and early embryonic development were detected.
GLP: no
Remarks: By analogy with a product of similar composition

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

Aluminium oxide:

Effects on fertility : Species: Rat, male and female
Strain: Sprague-Dawley
Application Route: Drinking water
Dose: 57 - 189 - 567 mg/kg
General Toxicity - Parent: NOAEL: ca. 567 mg/kg body weight
General Toxicity F1: NOAEL: ca. 57 mg/kg body weight
Method: Other
GLP: yes
Remarks: By analogy with a product of similar composition

Effects on foetal development : Species: Rat
Strain: wistar
Application Route: oral (gavage)
Dose: 126 - 251 - 503 mg/kg
Frequency of Treatment: 2 daily
General Toxicity Maternal: NOAEL: > 100 mg/kg body weight
Teratogenicity: NOAEL: 503 mg/kg body weight
Method: OECD Test Guideline 414
GLP: No information available.
Remarks: By analogy with a product of similar composition

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 16

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

No teratogenic effects to be expected.

Amorphous silicon dioxide:

- Effects on fertility : Test Type: One generation study
Species: Rat, male and female
Strain: Sprague-Dawley
Application Route: oral (feed)
Dose: 497 (m), 509 (f) mg/kg
General Toxicity - Parent: NOAEL: 497 mg/kg body weight
General Toxicity F1: NOAEL: 497 mg/kg body weight
Method: OECD Test Guideline 415
GLP: no
- Effects on foetal development : Test Type: Pre-natal
Species: Rat
Strain: wistar
Application Route: oral (gavage)
Dose: 13,5 - 62,7 - 292 - 1350mg/kg
General Toxicity Maternal: NOAEL: 1,350 mg/kg body weight
Teratogenicity: NOAEL: 1,350 mg/kg body weight
Method: OECD Test Guideline 414
GLP: no
- Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
No teratogenic effects to be expected.

C.I. Pigment White 6:

- Effects on fertility : Remarks: no data available
- Effects on foetal development : Test Type: Pre-natal
Species: Rat, female
Strain: wistar
Application Route: oral (gavage)
Dose: 100, 300, 1000 mg/kg bw
Duration of Single Treatment: 14 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight
Developmental Toxicity: NOAEL: 1,000 mg/kg body weight
Embryo-foetal toxicity: NOEL: 1,000 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes
Remarks: No significant adverse effects were reported
- Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
Did not show teratogenic effects in animal experiments.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 17

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

STOT - single exposure

Components:

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Aluminium oxide:

Target Organs: Lungs

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Amorphous silicon dioxide:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Vinyl acetate:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aluminium oxide:

Target Organs: Lungs

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Amorphous silicon dioxide:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 18

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Repeated dose toxicity

Components:

C.I. Pigment Black 7:

Species: Rat, female

NOAEL: 52 mg/kg bw/day

Application Route: oral (feed)

Exposure time: 1 a - 2 a

Number of exposures: daily

Dose: 2,05 g/kg of chow diet

Group: yes

Method: Other

GLP: No information available.

Remarks: No adverse effect has been observed in chronic toxicity tests.

Species: Rat, male

NOAEL: 0.0011 mg/l

LOAEL: 0.0071 mg/l

Application Route: Inhalation

Test atmosphere: dust/mist

Exposure time: 13 w

Number of exposures: 6 h per day; 5 d per week

Dose: 1,1 - 7,1 - 52,8 mg/m³

Group: yes

Method: Other

GLP: No information available.

Species: Mouse, male and female

Application Route: Skin contact

Exposure time: 12-18 m

Number of exposures: 3 times per week

Dose: 20% carbon black suspensions

Group: yes

Method: Other

GLP: no

Remarks: No adverse effect has been observed in chronic toxicity tests.

Aluminium oxide:

Species: Rat, male and female

NOAEL: 57 mg/kg

Application Route: Drinking water

Exposure time: 1 a

Number of exposures: continuously

Dose: 57 - 189 - 567 mg/kg

Group: yes

Method: OECD Test Guideline 426

GLP: yes

Remarks: By analogy with a product of similar composition

Species: Rat

LOAEL: 0.070 mg/l

Application Route: Inhalation

Exposure time: 6 m

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 19

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Number of exposures: 6 hr/day; 5 days a week

Dose: 15-30-50-70-100 mg Al/m³

Method: OECD Test Guideline 413

GLP: No information available.

Application Route: Skin contact

Remarks: The study is not necessary from a scientific perspective.

Amorphous silicon dioxide:

Species: Rat, male and female

NOAEL: 4000 - 4500 mg/kg bw/day

Application Route: oral (feed)

Exposure time: 13 w

Number of exposures: continuously

Dose: 0,5 - 2 - 6,7 % SI in diet

Group: yes

Method: OECD Test Guideline 408

GLP: yes

Species: Rat, male and female

NOAEL: 1,3 mg/m³

LOAEL: 0.0059 mg/l

Application Route: Inhalation

Exposure time: 13 w

Number of exposures: 6 hr/day; 5 days a week

Dose: 1,3 - 5,9 - 31 mg/m³

Group: yes

Method: OECD Test Guideline 413

GLP: yes

Application Route: Skin contact

Remarks: This information is not available.

C.I. Pigment White 6:

Species: Rat, male

NOEL: > 24000 mg/kg bw/day

Application Route: oral (gavage)

Exposure time: 29 d

Number of exposures: daily

Dose: 24000 mg/kg

Group: yes

Method: OECD Test Guideline 407

GLP: No information available.

Species: Rat, male and female

NOAEL: 0.01 mg/l

Application Route: Inhalation

Exposure time: 2 a

Number of exposures: 6 hours/day, 5 days/week

Dose: 0,0106 - 0,0507 - 0,250 mg/l

Group: yes

Method: Repeated Dose Toxicity (chronic Toxicity)

GLP: no

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 20

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Aspiration toxicity

Components:

C.I. Pigment Black 7:

No aspiration toxicity classification

Aluminium oxide:

No aspiration toxicity classification

Amorphous silicon dioxide:

No aspiration toxicity classification

C.I. Pigment White 6:

No aspiration toxicity classification

Experience with human exposure

Product:

General Information : The possible symptoms known are those derived from the labelling (see section 2).

Further information

Components:

C.I. Pigment White 6:

Remarks: Lung damage possible.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: no data available

Components:

C.I. Pigment Black 7:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l
End point: mortality
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: no
Method: OECD Test Guideline 203
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 21

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 5,600 mg/l
End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 202
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 201
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to fish (Chronic toxicity) : Remarks: not required

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: not required

Toxicity to microorganisms : EC0 (activated sludge): > 400 mg/l
End point: Bacteria toxicity (growth inhibition)
Exposure time: 3 h
Test Type: static test
Method: DIN 38412
GLP: no

Toxicity to soil dwelling organisms : Test Type: Other
Method: Other
GLP: No information available.
Remarks: This product does not have any known adverse effect on the soil organisms tested.

Aluminium oxide:

Toxicity to fish : NOEC (Salmo trutta (brown trout)): > 0.072 mg/l
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 0.071 mg/l
Exposure time: 48 h
Test Type: static test

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 22

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Analytical monitoring: yes
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): >= 0.052 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

EC50 (Pseudokirchneriella subcapitata (green algae)): 1.05 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes
Remarks: By analogy with a product of similar composition

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 56.48 mg/l
Exposure time: 7 d
Test Type: semi-static test
Analytical monitoring: yes
Method: Other
GLP: yes
Remarks: By analogy with a product of similar composition

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.076 mg/l
End point: Reproduction rate
Exposure time: 21 d
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 211
GLP: yes
Remarks: By analogy with a product of similar composition

Toxicity to microorganisms : Remarks: Not applicable

Toxicity to soil dwelling organisms : Remarks: Not applicable

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial organisms : Remarks: Not applicable

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 23

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Amorphous silicon dioxide:

Toxicity to fish : LL0 (Brachydanio rerio (zebrafish)): 10,000 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 203
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 202
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 201
GLP: yes
Remarks: By analogy with a product of similar composition
The details of the toxic effect relate to the nominal concentration.

Toxicity to fish (Chronic toxicity) : NOEC: 86.03 mg/l
Exposure time: 30 d
Method: Other
GLP: no
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 34.223 mg/l
Exposure time: 30 d
Method: Other
GLP: no
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 24

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Sediment toxicity : LC50: 148.41 mg/l
Duration: 14 d
Method: Other
GLP: no
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

C.I. Pigment White 6:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Method: EPA
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Method: OECD Test Guideline 203
GLP: No information available.
Remarks: The details of the toxic effect relate to the nominal concentration.

LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: no data available
Method: OECD Test Guideline 203
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Analytical monitoring: no data available
Method: OECD Test Guideline 202
GLP: no data available
Remarks: The details of the toxic effect relate to the nominal concentration.

LC50 (Acartia tonsa): > 10,000 mg/l
Exposure time: 48 h
Analytical monitoring: no data available
Method: ISO 14669 and PARCOM method
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 25

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

concentration.

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (microalgae)): 61 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: no
Method: EPA
GLP: No information available.
Remarks: The details of the toxic effect relate to the nominal concentration.

EC50 (*Skeletonema costatum* (marine diatom)): > 10,000 mg/l
End point: Growth rate
Exposure time: 72 h
Analytical monitoring: no data available
Method: ISO 10253
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to fish (Chronic toxicity) : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 7.31 mg/l
Exposure time: 28 d
Test Type: static test
Analytical monitoring: yes
Method: Other
GLP: No information available.
Remarks: By analogy with a product of similar composition

Toxicity to microorganisms : EC50 (activated sludge of a predominantly domestic sewage): > 1,000 mg/l
End point: Bacteria toxicity (respiration inhibition)
Exposure time: 3 h
Test Type: aquatic
Method: OECD Test Guideline 209
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

NOEC (activated sludge of a predominantly domestic sewage): $\geq 1,000$ mg/l
End point: Bacteria toxicity (respiration inhibition)
Exposure time: 3 h
Test Type: aquatic
Method: OECD Test Guideline 209
GLP: yes
Remarks: The details of the toxic effect relate to the nominal concentration.

Toxicity to soil dwelling organisms : Test Type: artificial soil
NOEC (*Folsomia candida*): 0,1 \rightarrow 10 %
Exposure time: 28 d
End point: mortality
Method: ISO 11267

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 26

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

GLP: no

Remarks: By analogy with a product of similar composition
This product does not have any known adverse effect on the
soil organisms tested.

Plant toxicity : NOEC: ≥ 10 %
Exposure time: 20 h
End point: Growth
Species: Lactuca sativa (lettuce)
Analytical monitoring: yes
Method: Other
GLP: no
Remarks: By analogy with a product of similar composition
No effect on the growth was observed.

Sediment toxicity : NOEC (Hyalella azteca (Scud)): ≥ 100000 %
Analytical monitoring: no
Sediment: artificial soil
Exposure duration: 28 d
Nominal / Measured: nominal
Basis for effect: mortality
Method: Other
GLP: no
Remarks: By analogy with a product of similar composition

NOEC: ≥ 14989 mg/kg dry weight (d.w.)
Analytical monitoring: no data available
Sediment: Natural sediment
Exposure duration: 10 d
Nominal / Measured: nominal
Basis for effect: mortality
Method: Other
GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Components:

C.I. Pigment Black 7:

Biodegradability : Remarks: Not applicable

Aluminium oxide:

Biodegradability : Remarks: Not applicable

Amorphous silicon dioxide:

Biodegradability : Remarks: Not applicable

C.I. Pigment White 6:

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 27

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Biodegradability : Remarks: Not applicable for inorganic compound.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: not tested.

Components:

C.I. Pigment Black 7:

Bioaccumulation : Remarks: Not applicable

Aluminium oxide:

Bioaccumulation : Remarks: Not applicable

C.I. Pigment White 6:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 20 - 200
Exposure time: 14 d
Concentration: 0.1 - 1 mg/l
Method: Other
GLP: No information available.
Remarks: Does not accumulate in organisms.

Partition coefficient: n-octanol/water : Remarks: inorganic

Mobility in soil

Product:

Distribution among environmental compartments : Remarks: not tested.

Components:

C.I. Pigment Black 7:

Distribution among environmental compartments : Adsorption/Soil
Medium: water - soil
Remarks: Not applicable

Aluminium oxide:

Distribution among environmental compartments : Remarks: Not applicable

C.I. Pigment White 6:

Mobility : Remarks: Adsorption to solid soil phase is possible.

Distribution among environmental compartments : Adsorption/Soil
Medium: water - soil
log Koc: 4.61

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 28

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

Method: Other

Other adverse effects

Product:

Results of PBT and vPvB assessment : Remarks: No information is available as no chemical safety report (CSR) is required.

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

Components:

C.I. Pigment Black 7:

Environmental fate and pathways : not available

Results of PBT and vPvB assessment : The substance is not identified as a PBT or as a vPvB substance.

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

Aluminium oxide:

Environmental fate and pathways : not available

Results of PBT and vPvB assessment : Remarks: Not applicable

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

Amorphous silicon dioxide:

Environmental fate and pathways : not available

Results of PBT and vPvB assessment : The substance is not identified as a PBT or as a vPvB substance.

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

C.I. Pigment White 6:

Environmental fate and pathways : not available

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Additional ecological information : Do not allow to enter ground water, waterways or waste water.

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 29

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of this product in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Regulations concerning reuse or disposal of used packaging materials must be observed.

SECTION 14. TRANSPORT INFORMATION

TDG	not restricted
IATA	not restricted
IMDG	not restricted

SECTION 15. REGULATORY INFORMATION

- NPRI Components** : Nickel compounds
Antimony compounds
Manganese Compound
Vinyl acetate

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
- CA BC OEL : Canada. British Columbia OEL
- CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 30

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWA ^{EV}	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); EC_x - Concentration associated with x% response; EL_x - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErC_x - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC₅₀ - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC₅₀ - Lethal Concentration to 50 % of a test population; LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date	:	09/19/2020
Date format	:	mm/dd/yyyy

The information contain herein is accurate to the best knowledge of Avient Corporation and its subsidiaries and affiliates. However, neither Avient nor any of its subsidiaries or affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of the Avient product is the sole responsibility of the user. Any material may present unknown hazards and should be used with caution. Due to possible changes in Avient products and applicable national and international regulations and laws, the status of the products could change. Although certain hazards are described herein, Avient and its subsidiaries and affiliates cannot guarantee that these are the only hazards that exist. This

SAFETY DATA SHEET



EVA 003.000% DC 17W1

Page 31

Substance key: 000000706413

Revision Date: 09/19/2020

Version : 1 - 1 / CDN

Date of printing :04/20/2022

information is only valid for the current intended use, and is not valid for such Avient product used in conjunction with any other materials or in any process.

CA / EN