

# SAFETY DATA SHEET

# 1. Identification

1. Identification			
Product identifier	LPS® 2 (Aerosol)		
Other means of identification			
Part Number	C30216		
Recommended use	An industrial lubricant designed to displace moisture from equipment, provide heavy-duty lubrication and rust prevention.		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Supplier	/Distributor information		
Manufacturer			
Company name	ITW Pro Brands		
Address	4647 Hugh Howell Rd.		
	Tucker, GA 30084		
Country	(U.S.A.)		
	Tel: +1 770-243-8800		
In Case of Emergency	1-800-424-9300		
	1-703-527-3887		
Website	www.lpslabs.com		
E-mail	lpssds@itwprobrands.com		
Supplier	ITW Permatex Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada 1-800-241-8334		
2. Hazard(s) identification			
Physical hazards	Flammable aerosols	Category 1	
	Gases under pressure	Compressed gas	
Health hazards	Not classified.		
Environmental hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	Extremely flammable aerosol. Co	ntains gas under pressure; may explode if heated.	
Precautionary statement	-		
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.		
Response	Wash hands after handling.		
Storage	Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F		

DisposalDispose of waste and residues in accordance with local authority requirements.Other hazardsCombustible.Supplemental informationNone known.

# 3. Composition/information on ingredients

#### **Mixtures**

50°C/122°F.

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light		64742-47-8	70 - 80
Petroleum Oil		64742-52-5	10 - 20
CARBON DIOXIDE		124-38-9	1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	No specific first aid measures noted.	
Ingestion	Not likely, due to the form of the product.	
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.	
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. Combustible.	

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

ACGIH			
Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist
Petroleum Oil (CAS 64742-52-5)	TWA	5 mg/m3	Oil mist
US. ACGIH Threshold Limit Value			
Components	Туре	Value	
CARBON DIOXIDE (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Canada. Alberta OELs (Occupatio			
Components	Туре	Value	
CARBON DIOXIDE (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Canada. British Columbia OELs. (	Occupational Exposure Limit	e for Chamical Substances C	heeunational Health and
		s for chemical Substances, c	
Safety Regulation 296/97, as ame	nded)		-
Safety Regulation 296/97, as ame Components	nded) Type	Value	Form
	nded) Type STEL	Value 15000 ppm	-
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9)	nded) Type STEL TWA	<b>Value</b> 15000 ppm 5000 ppm	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS	nded) Type STEL	Value 15000 ppm	-
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS	nded) Type STEL TWA TWA	Value 15000 ppm 5000 ppm 200 mg/m3	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	nded) Type STEL TWA TWA	Value 15000 ppm 5000 ppm 200 mg/m3	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21 Components CARBON DIOXIDE (CAS	nded) Type STEL TWA TWA TWA 7/2006, The Workplace Safety	Value 15000 ppm 5000 ppm 200 mg/m3 And Health Act)	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21 Components	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type	Value 15000 ppm 5000 ppm 200 mg/m3 And Health Act) Value	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21 Components CARBON DIOXIDE (CAS	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type STEL TWA	Value     15000 ppm     5000 ppm     200 mg/m3     And Health Act)     Value     30000 ppm     5000 ppm	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21) Components CARBON DIOXIDE (CAS 124-38-9)	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type STEL TWA	Value     15000 ppm     5000 ppm     200 mg/m3     And Health Act)     Value     30000 ppm     5000 ppm	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control of	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type STEL TWA of Exposure to Biological or Cl	Value     15000 ppm     5000 ppm     200 mg/m3     And Health Act)     Value     30000 ppm     5000 ppm	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21) Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control of Components CARBON DIOXIDE (CAS	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type STEL TWA of Exposure to Biological or Cl Type	Value   15000 ppm   5000 ppm   200 mg/m3   And Health Act)   Value   30000 ppm   5000 ppm   Value   Value   Value   Value   Value   Value   Value	Form
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21) Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control of Components CARBON DIOXIDE (CAS	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type STEL TWA of Exposure to Biological or Cl Type STEL TWA STEL TWA	Value     15000 ppm     5000 ppm     200 mg/m3     And Health Act)     Value     30000 ppm     5000 ppm     5000 ppm     30000 ppm     5000 ppm     5000 ppm     5000 ppm     5000 ppm     5000 ppm     5000 ppm	Form Non-aerosol.
Safety Regulation 296/97, as ame Components CARBON DIOXIDE (CAS 124-38-9) Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Canada. Manitoba OELs (Reg. 21 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control of Components CARBON DIOXIDE (CAS 124-38-9)	nded) Type STEL TWA TWA 7/2006, The Workplace Safety Type STEL TWA of Exposure to Biological or Cl Type STEL TWA STEL TWA	Value     15000 ppm     5000 ppm     200 mg/m3     And Health Act)     Value     30000 ppm     5000 ppm     5000 ppm     30000 ppm     5000 ppm     5000 ppm     5000 ppm     5000 ppm     5000 ppm     5000 ppm	Form Non-aerosol.

Components	Ministry of Labor - Regulation Type	Value	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Biological limit values	No biological exposure lin	its noted for the ingredient(s).	
Exposure guidelines			
Canada - British Columbi	a OELs: Skin designation		
Distillates Petroleum F 64742-47-8)	lydrotreated Light (CAS	Can be absorbed through the skin.	
Appropriate engineering controls	should be matched to cor or other engineering contr	ypically 10 air changes per hour) should be used. Ventilation rates ditions. If applicable, use process enclosures, local exhaust ventilation, ols to maintain airborne levels below recommended exposure limits. If een established, maintain airborne levels to an acceptable level.	
Individual protection measure	es, such as personal protect	ve equipment	
Eye/face protection	Wear safety glasses with	side shields (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemic	I resistant gloves.	
Other	Wear suitable protective of	lothing.	
Respiratory protection	If permissible levels are e air-supplied respirator.	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an	
Thermal hazards	Wear appropriate thermal	protective clothing, when necessary.	
General hygiene considerations	after handling the materia	Always observe good personal hygiene measures, such as washing and before eating, drinking, and/or smoking. Routinely wash work upment to remove contaminants.	

# 9. Physical and chemical properties

Appearance		
Physical state	Gas.	
Form	Aerosol.	
Color	Brown.	
Odor	Slight petroleum odor. Cherry.	
Odor threshold	Not established	
рН	Not applicable	
Melting point/freezing point	< -58 °F (< -50 °C)	
Initial boiling point and boiling range	383 °F (195 °C) @ 101 kPa	
Flash point	174.2 °F (79.0 °C) Tag Closed Cup (dispensed liquid)	
Evaporation rate	< 0.1 BuAc	
Flammability (solid, gas)	Flammable gas.	
Upper/lower flammability or exp	losive limits	
Flammability limit - lower (%)	0.6 %	
Flammability limit - upper (%)	7 %	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	< 0.05 mm Hg @ 20ºC (dispensed liquid)	
Vapor density	4.7 (air = 1)	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	< 3 %	

Partition coefficient (n-octanol/water)	< 1
Auto-ignition temperature	> 442.4 °F (> 228 °C)
Decomposition temperature	Not established
Viscosity	< 7 cSt
Viscosity temperature	77 °F (25 °C)
Other information	
Explosive properties	Not explosive.
Heat of combustion	> 30 kJ/g
Oxidizing properties	Not oxidizing.
Percent volatile	92 - 95 %
Specific gravity	0.82 - 0.86 @ 20°C
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition	Carbon oxides.

# 11. Toxicological information Information on likely routes of exposure

products

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

#### Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

	···· [································		
Components	Species	Test Results	
Distillates Petroleum Hydrotrea	ted Light (CAS 64742-47-8)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Inhalation			
Vapor			
LC50	Rat	> 4.5 mg/l, 4 Hours	
Petroleum Oil (CAS 64742-52-5	5)		
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 3.9 mg/l, 4 Hours	
Oral			
LD50	Rat	> 2000 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may cause	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		

Respiratory or skin sensitization	1			
Respiratory sensitization	Not a respiratory sensitizer.	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensiti			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen	by IARC, ACGIH, NTP, or OSHA.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not likely, due to the form of the product.			
Chronic effects	Prolonged inhalation may be harmful.			
Further information	None known.			
12. Ecological information	1			
Ecotoxicity	The product is not classified as environmentally h possibility that large or frequent spills can have a			
Components	Species	Test Results		
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) Aquatic				
Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours		
Persistence and degradability				
Bioaccumulative potential				
Partition coefficient n-octan LPS® 2 (Aerosol)	ol / water (log Kow) < 1			
Mobility in soil	No data available.			
Other adverse effects	None known.			
13. Disposal consideration	าร			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.			
14. Transport information				
TDG				
UN number	UN1950			
UN proper shipping name	Aerosols, flammable			
Transport hazard class(es) Class	2.1			
Subsidiary risk	-			
D	Net aveilele			

Environmental hazards

Packing group

No

UN1950

Not available.

Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	
IATA; IMDG; TDG	

General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

## 15. Regulatory information

#### Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

#### **Controlled Drugs and Substances Act**

Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases CARBON DIOXIDE (CAS 124-38-9) Precursor Control Regulations Not regulated.

International regulations

Additional information is given in the Safety Data Sheet.

Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable.		
Kyoto protocol		
CARBON DIOXIDE (C	CAS 124-38-9) Listed.	
Montreal Protocol	,	
Not applicable.		
Basel Convention		
Not applicable.		
ernational Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Europe	European List of Notified Chemical Substances (ELINCS)	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	
Korea	Existing Chemicals List (ECL)	
New Zealand	New Zealand Inventory	
	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	
*A "Vos" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)		

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information

Issue date Revision date Version #	11-01-2016 09-20-2017 02
Disclaimer	ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.

No

Yes

Yes