

ABS ABS 004.000% 7603M DRIFTWOOD

Page 1

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

SECTION 1. IDENTIFICATION

Identification of the	Clariant Plastics & Coatings Canada Inc.					
company:	2 Lone Oak Court					
	Toronto, Ontario, M9C 5R9					
	Telephone No.: +1 514-832-2559					
	Information of the substance/preparation:					
	BU Masterbatches					
	Product Stewardship, +1-704-331-7710					
	e-mail: SDS.NORAM@clariant.com					
	Emergency tel. number: +1 CANUTEC (613) 996-6666					
Trade name:	ABS ABS 004.000% 7603M DRIFTWOOD					
Material number:	SB82754409					
Chemical family:	Colourant preparation					

Carrier: ABS

Primary product use: Additive for plastic material processing

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Hazards Not Otherwise Classified: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Colourant preparation Carrier: ABS

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Styrene	100-42-5	< 0.1
C.I. Pigment Black 7	1333-86-4	0.25 - 0.5
N,N'-Ethylenedi(stearamide)	110-30-5	3 - 5
C.I. Pigment White 6	13463-67-7	25 - 40

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and by the Canadian WHMIS 2015 Hazardous Products Regulations (SOR/2015-17)., The hazardous ingredients of this product are encapsulated, therefore the material is not GHS classified for



ABS ABS 004.000% 7603M DRIFTWOOD

Page 2

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

health and environmental hazards as exposure is not expected., Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASUR	RES	
If inhaled	:	Move the victim to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical advice/ attention. Never give anything by mouth to an unconscious person.
In case of skin contact	:	Wash off immediately with plenty of water for at least 15 minutes. In case of burns apply cold water until pain subsides then seek medical advice. Burns must be treated by a physician. If molten polymer contact the skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burn. Skin absorption of reground pellets is unlikely.
In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately if irritation develops and persists.
If swallowed	:	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/ attention.
Most important symptoms and effects, both acute and delayed	:	The possible symptoms known are those derived from the labelling (see section 2). No additional symptoms are known.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	In case of fire hazardous decomposition products may be produced such as: Styrene Hydrogen cyanide (hydrocyanic acid) Acrylonitrile



ABS ABS 004.000% 7603M DRIFTWOOD

Page 3

bstance key: 000000656397		Revision Date: 01/12/20
rsion : 1 - 0 / CDN		Date of printing :05/28/20
		Carbon monoxide Carbon dioxide (CO2) Take measures to prevent the build up of electrostatic charge Dust can form an explosive mixture in air. Metal oxides Sulphur oxides
Further information	:	Combustible material In the event of fire and/or explosion do not breathe fumes. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Do not allow run-off from fire fighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.
CTION 6. ACCIDENTAL RELEA	ASI	E MEASURES
Personal precautions, protective equipment and emergency procedures	:	Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.
Environmental precautions	:	Do not allow contact with soil, surface or ground water. Prevent product from entering drains.
Methods and materials for containment and cleaning up	:	Avoid dust formation. Take measures to prevent the build up of electrostatic charge Sweep up and shovel into suitable containers for disposal. Take up uncontaminated material and pass on for further processing.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Take measures to prevent the build up of electrostatic charge.
Advice on safe handling	:	 Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation/personal protection. For personal protection see section 8. Avoid contact with skin, eyes and clothing. Use only with adequate ventilation. When handling hot melts use suitable protective clothing. Avoid dust formation. Keep away from sources of ignition. Lead off electrostatic charges.



ABS ABS 004.000% 7603M DRIFTWOOD

Page 4

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020
Conditions for safe storage :	Keep container tightly closed in a cool, well-ventilated place. Protect from moisture. Keep away from direct sunlight.
Technical : measures/Precautions	Store in a cool, dry, well-ventilated area. Keep container sealed when not in use. Keep in an area equipped with sprinklers. Minimize dust generation and accumulation.
Materials to avoid :	not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
C.I. Pigment Black 7	1333-86-4	TWA	3.5 mg/m3	CA AB OEL
		TWA	3.5 mg/m3	CA BC OEL
	Further inform	ation: IARC '2B'	applies to substance	s deemed
	possibly carcir	nogenic to huma	ns.	
		TWAEV	3.5 mg/m3	CA ON OEL
		TWAEV	3.5 mg/m3	CA QC OEL
		TWA	3 mg/m3	CA BC OEL
		(Inhalable)		
			applies to substance	s deemed
		nogenic to huma		
C.I. Pigment White 6	13463-67-7	TWA	10 mg/m3	CA AB OEL
			nal exposure limit is l	
			nent to compensate for	or unusual
	work schedule	s is not required		
		TWA	10 mg/m3	CA BC OEL
	Further inform	ation: IARC '2B'	applies to substance	s deemed
			ns., The 8-hour TWA	
			substance also has a	an 8-hour TWA
	of 3 mg/m3 for	the respirable f		
		TWAEV (Total)	10 mg/m3	CA ON OEL
		TWAEV	10 mg/m3	CA QC OEL
		(total dust)	_	
	Further inform	ation: The stand	ard corresponds to d	ust containing
	no asbestos a %.	nd the percentaç	ge in crystalline silica	is less than 1
		TWAEV	10 mg/m3	CA QC OEL
		(total dust)		
	Further inform		ard corresponds to d	ust containing
			ge in crystalline silica	



ABS ABS 004.000% 7603M DRIFTWOOD

ostance key: 000000656397				ate: 01/12/2017
sion : 1 - 0 / CDN			Date of printi	ng :05/28/2020
Charac	%.		25	
Styrene	100-42-5		35 ppm	
		STEV	100 ppm	
		TWA	35 ppm	CA ON OE
		STEL	100 ppm	CA ON OE
		TWA	20 ppm 85 mg/m3	CA AB OE
		STEL	40 ppm 170 mg/m3	CA AB OE
		TWA	50 ppm	CA BC OE
	Further infor	mation: IARC '2	B' applies to substa	nces deemed
	possibly car	cinogenic to hun	nans.	
		STEL	75 ppm	CA BC OE
	Further infor	mation: IARC '2	B' applies to substa	nces deemed
	possibly car	cinogenic to hun	nans.	
		TWA	35 ppm	CA ON OE
		STEL	100 ppm	CA ON OE
		TWAEV	50 ppm 213 mg/m3	CA QC OE
	Further infor	mation: Skin (pe	ercutaneous), Carcir	nogenic effect
			of studies relating t	
	carcinogeno	city of these sub	ostances in animals	are not
	necessarily	applicable to hui	mans.	
		STEV	100 ppm	CA QC OE
		0.121	426 mg/m3	
	Further infor			
		mation: Skin (pe	426 mg/m3	nogenic effect
	detected in a carcinogeno	mation: Skin (pe animals. Results city of these sub	426 mg/m3 ercutaneous), Carcir of studies relating to ostances in animals	nogenic effect to the
	detected in a carcinogeno	mation: Skin (pe animals. Results city of these sub	426 mg/m3 ercutaneous), Carcir of studies relating to ostances in animals	nogenic effect to the
Engineering measures	detected in a carcinogeno necessarily : Use only in	mation: Skin (pe animals. Results city of these sub applicable to hu	426 mg/m3 ercutaneous), Carcir of studies relating to ostances in animals	nogenic effect to the are not
Engineering measures	detected in a carcinogeno necessarily : Use only in ventilation.	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w	426 mg/m3 ercutaneous), Carcir of studies relating to ostances in animals mans.	nogenic effect to the are not aust
Engineering measures	detected in a carcinogeno necessarily : Use only in ventilation. Provide app	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mac	nogenic effect to the are not aust
Engineering measures	detected in a carcinogeno necessarily : Use only in ventilation. Provide app places whe	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated.	nogenic effect to the are not aust hinery and at
Engineering measures	 detected in a carcinogeno necessarily a Use only in ventilation. Provide applaces whe Use engine 	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mac	nogenic effect to the are not aust hinery and at eral exhaust to
Engineering measures	 detected in a carcinogeno necessarily a Use only in ventilation. Provide applaces whe Use engine 	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach penerated. uch as local or gene	nogenic effect to the are not aust hinery and at eral exhaust to
Engineering measures Personal protective equipme	 detected in a carcinogeno necessarily a Use only in ventilation. Provide applaces whe Use engine maintain air 	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach penerated. uch as local or gene	nogenic effect to the are not aust hinery and at eral exhaust to
Personal protective equipme	detected in a carcinogeno necessarily : : Use only in ventilation. Provide app places whe Use engine maintain air nt : Use NIOSH	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su borne concentra	426 mg/m3 ercutaneous), Carcir of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or generations below exposu- ed respirators follow	nogenic effect to the are not aust hinery and at eral exhaust to are limits.
Personal protective equipme	detected in a carcinogeno necessarily : : Use only in ventilation. Provide app places whe Use engine maintain ain nt : Use NIOSH manufactur	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su borne concentra	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach penerated. uch as local or generations below exposu	nogenic effect to the are not aust hinery and at eral exhaust to are limits.
Personal protective equipme	detected in a carcinogeno necessarily : : Use only in ventilation. Provide app places whe Use engine maintain ain nt : Use NIOSH manufactur generated.	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su rborne concentra	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or generations below exposu- ed respirators follow lations where dust o	nogenic effect to the are not aust hinery and at eral exhaust to ire limits. ing or fume may be
Personal protective equipme	detected in a carcinogeno necessarily : Use only in ventilation. Provide app places whe Use engine maintain air nt : Use NIOSH manufactur generated. Use respira	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su rborne concentra M/MSHA approve er's recommend	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or gene ations below exposu	nogenic effect to the are not aust hinery and at eral exhaust to ire limits. ing or fume may be
Personal protective equipme	detected in a carcinogeno necessarily : Use only in ventilation. Provide app places whe Use engine maintain air nt : Use NIOSH manufactur generated. Use respira	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su rborne concentra	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or gene ations below exposu	nogenic effect to the are not aust hinery and at eral exhaust to ire limits. ing or fume may be
Personal protective equipme Respiratory protection	detected in a carcinogeno necessarily : : Use only in ventilation. Provide app places whe Use engine maintain air nt : Use NIOSH manufactur generated. Use respira	mation: Skin (pe animals. Results city of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su rborne concentra M/MSHA approve er's recommend	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or gene ations below exposu	nogenic effect to the are not aust hinery and at eral exhaust to ire limits. ing or fume may be
Personal protective equipme	 detected in a carcinogeno necessarily i Use only in ventilation. Provide app places whe Use engine maintain air Use NIOSH manufactur generated. Use respira at elevated 	mation: Skin (per animals. Results acity of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su rborne concentra M/MSHA approve er's recommend tory protective e temperatures (s	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or generations below exposu- ed respirators follow lations where dust of equipment when using see section 8).	nogenic effect to the are not aust hinery and at eral exhaust to are limits.
Personal protective equipme Respiratory protection Hand protection	 detected in a carcinogeno necessarily in ventilation. Provide app places whe Use engine maintain air Use NIOSH manufactur generated. Use respira at elevated Nitrile rubbo 	mation: Skin (per animals. Results ocity of these sub applicable to hun area provided w propriate exhaus re dust can be g ering controls su rborne concentra M/MSHA approve er's recommend tory protective e temperatures (s	426 mg/m3 ercutaneous), Carcin of studies relating to ostances in animals mans. with appropriate exhi- st ventilation at mach generated. uch as local or gene ations below exposu	nogenic effect to the are not aust hinery and at oral exhaust to are limits. ing or fume may be ng this product



ABS ABS 004.000% 7603M DRIFTWOOD

Page 6

Substance key: 00000065639	7	Revision Date: 01/12/2017
Version : 1 - 0 / CDN		Date of printing :05/28/2020
Skin and body protection	:	Wear protective clothing, including long sleeves and gloves, to prevent skin contact. When handling hot melts use suitable protective clothing.
Hygiene measures	:	The usual Industrial Hygiene precautions must be taken during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during work intervals and after work.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Granules
Colour	:	brown
Odour	:	characteristic
Odour Threshold	:	Not applicable
рН	:	Not applicable
Melting point	:	> 90 °C
Boiling point	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	not determined
Self-ignition	:	Not applicable
Upper explosion limit	:	not tested.
Lower explosion limit	:	not tested.
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	not available
Density	:	not tested.
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	This property is not applicable for mixtures.
Decomposition temperature	:	To the best of our current knowledge, no thermal



ABS ABS 004.000% 7603M DRIFTWOOD

Page 7

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020
	decomposition of the product is expected if it is processed according to good manufacturing practices. See section 10.4. "Conditions to avoid"
Viscosity	
Viscosity, dynamic :	Not applicable
Viscosity, kinematic :	Not applicable
Explosive properties :	no data available no data available
Oxidizing properties :	not available
Surface tension :	Not relevant
Particle size :	Product specific

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Heating can release hazardous gases. Keep away from heat, sparks, open flames, and other sources of ignition. If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Incompatible materials	:	no data available Strong acids and strong bases Strong oxidizing agents Strong acids and oxidizing agents
Hazardous decomposition products	:	Possible in traces: Nitrogen oxides (NOx) No hazardous decomposition products if stored and handled as prescribed



ABS ABS 004.000% 7603M DRIFTWOOD

Page 8

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity		
Components:		
Styrene: Acute oral toxicity	:	LD50 (Rat): 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 11.8 mg/l Exposure time: 4 h
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg
C.I. Pigment Black 7:		
Acute oral toxicity	:	LD50 (Rat, male and female): > 8,000 mg/kg Method: OECD Test Guideline 401 GLP: no
Acute inhalation toxicity	:	LC0 (Rat): > 0.0046 mg/l Exposure time: 4 h Method: Other GLP: No information available.
Acute dermal toxicity	:	Remarks: not reasonable
C.I. Pigment White 6:		
Acute oral toxicity	:	LD50 (Rat, female): > 5,000 mg/kg Method: OECD Test Guideline 425 GLP: no
Acute inhalation toxicity	:	LC50 (Rat, male and female): 3.4 - 5.1 mg/l Exposure time: 4 h Method: OECD Test Guideline 403 GLP: no
Acute dermal toxicity	:	Assessment: The substance or mixture has no acute dermal toxicity Remarks: Not applicable

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

Styrene: Result: Skin irritation

CLARIANT

ABS ABS 004.000% 7603M DRIFTWOOD

Page 9

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

C.I. Pigment Black 7:

Species: Rabbit Exposure time: 4 - 24 h Method: OECD Test Guideline 404 Result: No skin irritation GLP: no

C.I. Pigment White 6:

Species: Rabbit Exposure time: 4 h Method: OECD Test Guideline 404 Result: No skin irritation GLP: no

Serious eye damage/eye irritation

Product:

Result: No eye irritation

Components:

Styrene: Result: Eye irritation

C.I. Pigment Black 7:

Species: rabbit eye Result: No eye irritation Method: OECD Test Guideline 405 GLP: no

C.I. Pigment White 6:

Species: rabbit eye Result: non-irritant Method: OECD Test Guideline 405 GLP: No information available.

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

Styrene: Result: Does not cause skin sensitisation.

CLARIANT

ABS ABS 004.000% 7603M DRIFTWOOD

Page 10

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

C.I. Pigment Black 7:

Test Type: Buehler Test Exposure routes: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: non-sensitizing GLP: yes

C.I. Pigment White 6:

Test Type: Mouse local lymphnode assay Exposure routes: Skin contact Species: Mouse Method: OECD Test Guideline 429 Result: non-sensitizing GLP: No information available.

Test Type: Buehler Test Exposure routes: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: non-sensitizing GLP: yes

Test Type: Respiratory system Exposure routes: inhalation (dust/mist/fume) Species: Mouse Method: Other Result: Does not cause respiratory sensitisation. GLP: No information available.

Germ cell mutagenicity

Components:

Styrene:

Genotoxicity in vitro	:	Remarks: no data available
Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.
C.I. Pigment Black 7:		
Genotoxicity in vitro	:	Test Type: Ames test Species: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes
	:	Test Type: Ames test Species: Escherichia coli Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471



ABS ABS 004.000% 7603M DRIFTWOOD

stance key: 000000656397		Revision Date: 01/12/201
sion : 1 - 0 / CDN		Date of printing :05/28/202
		Result: negative GLP: yes
Genotoxicity in vivo	:	Result: ambiguous
Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.
C.I. Pigment White 6:		
Genotoxicity in vitro	:	Test Type: Ames test Species: Salmonella typhimurium Concentration: 333 - 5000 µg/plate Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes
	:	Test Type: Ames test Species: Escherichia coli Concentration: 333 - 5000 µg/plate Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes
Genotoxicity in vivo	:	Test Type: Micronucleus test Species: Mouse (male and female) Strain: ICR Cell type: Erythrocytes Application Route: oral (gavage) Exposure time: single treatment Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 474 Result: negative GLP: yes
Germ cell mutagenicity - Assessment	:	It is concluded that the product is not mutagenic based on evaluation of several mutagenicity tests.
Carcinogenicity		
Components:		
Styrene:		
Carcinogenicity - Assessment	:	Not classifiable as a human carcinogen.
C.I. Pigment Black 7:		
Carcinogenicity - Assessment	:	Not classifiable as a human carcinogen.



ABS ABS 004.000% 7603M DRIFTWOOD

Page 12

ostance key: 000000656397 rsion : 1 - 0 / CDN		Revision Date: 01/12/20 Date of printing :05/28/202
		Bate of printing toor 20/20/20
C.I. Pigment White 6: Carcinogenicity - Assessment	Not clas	sifiable as a human carcinogen.
Reproductive toxicity		
Components:		
Styrene:		
Effects on fertility		
	Remark are not i	s: Based on available data, the classification criteria net.
Reproductive toxicity - Assessment		oductive toxicity to be expected. ed of damaging the unborn child.
C.I. Pigment Black 7:		
Effects on fertility		
	Remark perspec	s: The study is not necessary from a scientific tive.
Effects on foetal development	Remark perspec	s: The study is not necessary from a scientific tive.
Reproductive toxicity - Assessment		oductive toxicity to be expected. ogenic effects to be expected.
C.I. Pigment White 6:		
Effects on fertility		
	Remark perspec	s: The study is not necessary from a scientific tive.
Effects on foetal development	Remark perspec	s: The study is not necessary from a scientific tive.
Reproductive toxicity -		oductive toxicity to be expected. ogenic effects to be expected.

Components:

Styrene:

Assessment: May cause respiratory irritation.

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.



ABS ABS 004.000% 7603M DRIFTWOOD

Page 13

Substance key: 00000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

Styrene:

Assessment: Causes damage to organs through prolonged or repeated exposure.

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

Styrene: Remarks: This information is not available.

C.I. Pigment Black 7:

Species: Rat, female NOAEL: 52 mg/kg Application Route: oral (feed) Exposure time: 1 a - 2 a Number of exposures: daily Dose: 2,05 g/kg of chow diet Group: yes Method: Repeated Dose Toxicity (chronic Toxicity) GLP: No information available. Remarks: The product is non-toxic.

Species: Rat, male NOAEL: 0.0011 mg/l LOAEL: 0.0071 mg/l Application Route: Inhalation Exposure time: 13 w Number of exposures: 6 h per day; 5 d per week Dose: 1,1 - 7,1 - 52,8 mg/m3 Group: yes Method: OECD Test Guideline 413 GLP: No information available.

Species: Mouse, male and female



ABS ABS 004.000% 7603M DRIFTWOOD

Page 14

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

Application Route: Skin contact Exposure time: 12-18 m Number of exposures: 3 times per week Dose: 20% carbon black suspensions Group: yes Method: Repeated Dose Toxicity (chronic Toxicity) GLP: no Remarks: The product is non-toxic.

C.I. Pigment White 6:

Species: Rat, male NOAEL: 24,000 mg/kg Application Route: oral (gavage) Exposure time: 29 d Number of exposures: daily Dose: 24000 mg/kg Group: yes Method: OECD Test Guideline 407 GLP: No information available.

Species: Rat, male and female NOAEL: 0.01 mg/l Application Route: Inhalation Exposure time: 2 a Number of exposures: 6 hours/day, 5 days/week Dose: 0,0106 - 0,0507 - 0,250 mg/l Group: yes Method: Repeated Dose Toxicity (chronic Toxicity) GLP: no

Application Route: Skin contact Remarks: The study is not necessary from a scientific perspective.

•

Aspiration toxicity

Components:

Styrene:

May be fatal if swallowed and enters airways.

C.I. Pigment Black 7:

No aspiration toxicity classification

C.I. Pigment White 6:

No aspiration toxicity classification

Experience with human exposure

Product:

General Information

The possible symptoms known are those derived from the labelling (see section 2).

CLARIANT

ABS ABS 004.000% 7603M DRIFTWOOD

Page 15

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

Further information

Components:

C.I. Pigment White 6:

Remarks: Lung damage possible.

SECTION 12. ECOLOGICAL INFORMATION

:

Ecotoxicity

Product:

Toxicity to fish

Remarks: no data available

Components:

Styrene:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 4.02 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 4.7 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 4.9 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	Remarks: no data available
•	:	Remarks: no data available
Toxicity to microorganisms	:	EC50 (other bacteria): 500 mg/l Exposure time: 0.5 h
Toxicity to soil dwelling organisms	:	Remarks: Not applicable
Plant toxicity	:	Remarks: Not applicable
Sediment toxicity	:	Remarks: Not applicable
Toxicity to terrestrial organisms	:	Remarks: Not applicable
C.I. Pigment Black 7:		
Toxicity to fish	:	LC0 (Brachydanio rerio (zebrafish)): 1,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no Method: OECD Test Guideline 203 GLP: yes



ABS ABS 004.000% 7603M DRIFTWOOD

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020
	Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 5,600 mg/l Exposure time: 24 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 202 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
	NOEC (Daphnia magna (Water flea)): 3,200 mg/l Exposure time: 24 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 202 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to algae :	EC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 10,000 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 201 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
	NOEC (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 10,000 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 201 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to fish (Chronic : toxicity)	Remarks: not reasonable
Toxicity to daphnia and other : aquatic invertebrates (Chronic toxicity)	Remarks: not reasonable
Toxicity to microorganisms :	EC0 (activated sludge, domestic): > 400 mg/l Exposure time: 3 h Test Type: static test Analytical monitoring: no Method: DEV L 3



ABS ABS 004.000% 7603M DRIFTWOOD

GLP: no Remarks: The details of the toxic effect relate to the nominal concentration. Sediment toxicity : Remarks: Not applicable C.I. Pigment White 6:	ostance key: 000000656397	Revision Date: 01/12/201
Remarks: The details of the toxic effect relate to the nominal concentration. Sediment toxicity : Remarks: Not applicable C1. Pigment White 6: : Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: EPA GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: CECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Opcorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Opprindon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Me	sion : 1 - 0 / CDN	Date of printing :05/28/202
C1. Pigment White 6: Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: EPA GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available. Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: yes CECD Test Guideline 202 GLP: no		Remarks: The details of the toxic effect relate to the nominal
Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: EPA GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: CECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available. Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Dyprindon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. Test Type: set taic test Analytical monitoring: no data available Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.<	Sediment toxicity	: Remarks: Not applicable
Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: EPA GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal 	C.I. Pigment White 6:	
Exposure time: 96 hTest Type: static testAnalytical monitoring: noMethod: OECD Test Guideline 203GLP: No information available.Remarks: The details of the toxic effect relate to the nominal concentration.LC50 (Cyprinodon variegatus (sheepshead minnow)): >10,000 mg/lExposure time: 96 hTest Type: semi-static testAnalytical monitoring: no data available Method: OECD Test Guideline 203GLP: yesRemarks: The details of the toxic effect relate to the nominal concentration.Toxicity to daphnia and other aquatic invertebrates:LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal concentration.LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal concentration.LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Method: ISO 14669 and PARCOM method GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.	Toxicity to fish	Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: EPA GLP: yes Remarks: The details of the toxic effect relate to the nominal
 10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Remarks: The details of the toxic effect relate to the nominal concentration. LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Method: ISO 14669 and PARCOM method GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration. 		Exposure time: 96 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 203 GLP: No information available. Remarks: The details of the toxic effect relate to the nominal
aquatic invertebratesExposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal concentration.LC50 (Acartia tonsa): > 10,000 mg/l Exposure time: 48 h Analytical monitoring: no data available Method: ISO 14669 and PARCOM method GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.		10,000 mg/l Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no data available Method: OECD Test Guideline 203 GLP: yes Remarks: The details of the toxic effect relate to the nominal
Exposure time: 48 h Analytical monitoring: no data available Method: ISO 14669 and PARCOM method GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.		Exposure time: 48 h Test Type: static test Analytical monitoring: no data available Method: OECD Test Guideline 202 GLP: no data available Remarks: The details of the toxic effect relate to the nominal
Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 61 mg/		Exposure time: 48 h Analytical monitoring: no data available Method: ISO 14669 and PARCOM method GLP: yes Remarks: The details of the toxic effect relate to the nominal
	Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (microalgae)): 61 mg/



ABS ABS 004.000% 7603M DRIFTWOOD

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020
	End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no Method: EPA GLP: No information available. Remarks: The details of the toxic effect relate to the nominal concentration.
	EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l End point: Growth rate Exposure time: 72 h Analytical monitoring: no data available Method: ISO 10253 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to fish (Chronic : toxicity)	LC50 (Oncorhynchus mykiss (rainbow trout)): 7.31 mg/l Exposure time: 28 d Test Type: static test Analytical monitoring: yes Method: Other GLP: No information available. Remarks: By analogy with a product of similar composition
Toxicity to daphnia and other : aquatic invertebrates	Remarks: Not applicable
(Chronic toxicity) Toxicity to microorganisms :	EC50 (activated sludge of a predominantly domestic sewage): > 1,000 mg/l End point: Bacteria toxicity (respiration inhibition) Exposure time: 3 h Test Type: aquatic Method: OECD Test Guideline 209 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
	NOEC (activated sludge of a predominantly domestic sewage): >= 1,000 mg/l End point: Bacteria toxicity (respiration inhibition) Exposure time: 3 h Test Type: aquatic Method: OECD Test Guideline 209 GLP: yes Remarks: The details of the toxic effect relate to the nominal concentration.
Toxicity to soil dwelling : organisms	Test Type: artificial soil NOEC (Folsomia candida): 0,1 ->= 10 % Exposure time: 28 d End point: mortality



ABS ABS 004.000% 7603M DRIFTWOOD

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020
	Method: ISO 11267 GLP: no Remarks: By analogy with a product of similar composition This product does not have any known adverse effect on the soil organisms tested.
Plant toxicity :	NOEC (Lactuca sativa (lettuce)): >= 10 % Exposure time: 20 h End point: Growth Analytical monitoring: yes Method: Other GLP: no Remarks: By analogy with a product of similar composition No effect on the growth was observed.
Sediment toxicity :	NOEC (Hyalella azteca (Scud)): >= 100000 % Analytical monitoring: no Sediment: artificial soil Exposure duration: 28 d Nominal / Measured: nominal Basis for effect: mortality Test substance: artificial soil Analytical monitoring: no Method: Other GLP: no Remarks: By analogy with a product of similar composition NOEC: >= 14989 mg/kg dry weight (d.w.) Analytical monitoring: no data available Sediment: Natural sediment Exposure duration: 10 d Nominal / Measured: nominal Basis for effect: mortality Test substance: Natural sediment Analytical monitoring: no data available Method: Other GLP: yes
Toxicity to terrestrial : organisms	Remarks: Not applicable
Persistence and degradability	
Components:	
Styrene: Biodegradability :	aerobic Result: Readily biodegradable. Biodegradation: 70.9 % Exposure time: 28 d
C.I. Pigment Black 7: Biodegradability :	Remarks: Not applicable



ABS ABS 004.000% 7603M DRIFTWOOD

stance key: 000000656397		Revision Date: 01/12/201
sion : 1 - 0 / CDN		Date of printing :05/28/202
C.I. Pigment White 6:		
Biodegradability		Remarks: Not applicable for inorganic compound.
	•	
Bioaccumulative potential		
Product:		
Bioaccumulation	:	Remarks: not tested.
Components:		
Styrene:		
Bioaccumulation	:	Remarks: Due to the distribution coefficient n-octanol/water,
	-	accumulation in organisms is not expected.
C.I. Pigment Black 7:		
Bioaccumulation	:	Remarks: Not applicable
C.I. Pigment White 6:		
Bioaccumulation	:	Species: Oncorhynchus mykiss (rainbow trout)
		Bioconcentration factor (BCF): 20 - 200
		Exposure time: 14 d
		Concentration: 0.1 - 1 mg/l Method: Other
		GLP: No information available.
		Remarks: Does not accumulate in organisms.
Mobility in soil		
Product:		
Distribution among		Remarks: not tested.
environmental compartments	•	
Components:		
Styrene:		
Distribution among	:	Remarks: no data available
environmental compartments		
C.I. Pigment Black 7:		
Mobility	:	Remarks: Known distribution to environmental compartments
Distribution among	:	Adsorption/Soil
environmental compartments	•	Medium: water - soil
•		Remarks: Not applicable
C.I. Pigment White 6:		
on righten white 0.		Remarks: Adsorption to solid soil phase is possible.
Mobility		
Mobility		
Distribution among	:	Adsorption/Soil
Mobility Distribution among environmental compartments	:	Adsorption/Soil Medium: water - soil log Koc: 4.61



ABS ABS 004.000% 7603M DRIFTWOOD

ubstance key: 00000065639 ersion : 1 - 0 / CDN	7 Revision Date: 01/12/20 Date of printing :05/28/202
	Method: Other
Other adverse effects	
Product:	
Results of PBT and vPvB assessment	: Remarks: No information is available as no chemical safety report (CSR) is required.
Additional ecological information	: Do not allow to enter ground water, waterways or waste wate
Components:	
Styrene:	
Environmental fate and pathways	: no data available
Results of PBT and vPvB assessment	: This substance is not considered to be persistent, bioaccumulating and toxic (PBT).
Additional ecological information	: The product should not be allowed to enter drains, water courses or the soil.
C.I. Pigment Black 7:	
Environmental fate and pathways	: not available
Results of PBT and vPvB assessment	: The substance is not identified as a PBT or as a vPvB substance.
Additional ecological information	: Do not allow to enter ground water, waterways or waste wate
C.I. Pigment White 6:	
Environmental fate and pathways	: not available
Results of PBT and vPvB assessment	: The substance is inorganic, thus a PBT and vPvB criteria assessment is not applicable according to Annex XIII of Regulation (EC) 1907/2006.
Additional ecological	: Do not allow to enter ground water, waterways or waste wate

Waste from residues	:	Dispose of this product in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Regulations concerning reuse or disposal of used packaging materials must be observed.



ABS ABS 004.000% 7603M DRIFTWOOD

Page 22

Substance key: 00000065639	P7 Revision Date: 01/12/2017		
Version : 1 - 0 / CDN	Date of printing :05/28/2020		
TDG	not restricted		
ΙΑΤΑ	not restricted		
IMDG	not restricted		
SECTION 15. REGULATORY INFORMATION			
NPRI Components	: Zinc compounds Styrene		
The components of this product are reported in the following inventories:			
DSL	: All components of this product are on the Canadian DSL		

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System



ABS ABS 004.000% 7603M DRIFTWOOD

Page 23

Substance key: 000000656397	Revision Date: 01/12/2017
Version : 1 - 0 / CDN	Date of printing :05/28/2020

Revision Date : 01/12/2017

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application. NO EXPRESS OR IMPLIED WARRANTY IS MADE OF THE MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE OF ANY PRODUCT OR SERVICE. Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

CA / EN