

ABS GP35 004.000% BEIGE 748SW-B

Page 1

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

SECTION 1. IDENTIFICATION

Identification of the Avient Colorants Canada Inc.

company: 2 Lone Oak Court

Toronto, Ontario M9C 5R9, Telephone No.: +1 416-847-7000

Information of the substance/preparation:

Product Stewardship

e-mail: SDS.NORAMMB@avient.com

Emergency tel. number: 1-800-424-9300 (CHEMTREC)

Trade name: ABS GP35 004.000% BEIGE 748SW-B

Material number: SB83765620

Synonyms: ABS GP35 004.000% BEIGE 748SW-B (06ABS-343)

Chemical family: Colourant preparation

Carrier: ABS

Primary product use: Additive for plastic material processing

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Hazards Not Otherwise Classified:

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Colourant preparation

Carrier: ABS

Components

Chemical name	CAS-No.	Concentration (% w/w)
C.I. Pigment Yellow 164	68412-38-4	0.1 - 1
C.I. Pigment Black 28	68186-91-4	0.1 - 1
Aluminium oxide	1344-28-1	0.1 - 1
N,N'-Ethylenedi(stearamide)	110-30-5	1 - 5
C.I. Pigment White 6	13463-67-7	10 - 30

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and by the Canadian WHMIS 2015 Hazardous Products Regulations (SOR/2015-17)., The hazardous ingredients of this product are encapsulated, therefore the material is not



ABS GP35 004.000% BEIGE 748SW-B

Page 2

Substance key: 000000645369 Revision Date: 09/19/2020 Version: 1-2/CDN Date of printing :05/02/2023

GHS classified for health and environmental hazards as exposure is not expected., Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

If inhaled Move the victim to fresh air.

> Give oxygen or artificial respiration if needed. Get immediate medical advice/ attention.

Never give anything by mouth to an unconscious person.

In case of skin contact Wash off immediately with plenty of water for at least 15

minutes.

In case of burns apply cold water until pain subsides then

seek medical advice.

Burns must be treated by a physician.

If molten polymer contact the skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burn. Skin absorption of

reground pellets is unlikely.

Rinse immediately with plenty of water, also under the eyelids, In case of eye contact

for at least 15 minutes.

Get medical attention immediately if irritation develops and

persists.

If swallowed Rinse mouth.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

Get medical advice/ attention.

Most important symptoms and effects, both acute and

delayed

The possible symptoms known are those derived from the

labelling (see section 2).

No additional symptoms are known.

Treat symptomatically. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

In case of fire hazardous decomposition products may be

produced such as:

Styrene

Hydrogen cyanide (hydrocyanic acid)

Acrylonitrile



ABS GP35 004.000% BEIGE 748SW-B

Page 3

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Carbon monoxide Carbon dioxide (CO2)

Take measures to prevent the build up of electrostatic charge.

Dust can form an explosive mixture in air.

Metal oxides Zinc oxide

Further information : Combustible material

In the event of fire and/or explosion do not breathe fumes. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion

Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Do not allow run-off from fire fighting to enter drains or water

courses.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for firefighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Refer to protective measures listed in sections 7 and 8.

Avoid contact with skin, eyes and clothing.

Wash thoroughly after handling.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent product from entering drains.

Methods and materials for containment and cleaning up

Avoid dust formation.

Take measures to prevent the build up of electrostatic charge. Sweep up and shovel into suitable containers for disposal. Take up uncontaminated material and pass on for further

processing.

After cleaning, flush away traces with water.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion

Advice on protection against : Take measures to prevent the build up of electrostatic charge.

Advice on safe handling

Handle in accordance with good industrial hygiene and safety

practice.

Use only with adequate ventilation/personal protection.

For personal protection see section 8. Avoid contact with skin, eyes and clothing.

Use only with adequate ventilation.

When handling hot melts use suitable protective clothing. Avoid dust formation. Keep away from sources of ignition.



ABS GP35 004.000% BEIGE 748SW-B

Page 4

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Lead off electrostatic charges.

Conditions for safe storage : Keep container tightly closed in a cool, well-ventilated place.

Protect from moisture.

Keep away from direct sunlight.

Further information on storage conditions

Store in a cool, dry, well-ventilated area. Keep container

sealed when not in use.

Keep in an area equipped with sprinklers. Minimize dust generation and accumulation.

Materials to avoid : not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N,N'-Ethylenedi(stearamide)	110-30-5	TWA	10 mg/m3	CA AB OEL
		TWA	10 mg/m3	CA BC OEL
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
C.I. Pigment Yellow 164	68412-38-4	TWA	0.5 mg/m3 (antimony)	CA AB OEL
		TWA	0.2 mg/m3 (Manganese)	CA AB OEL
		TWAEV	0.5 mg/m3 (antimony)	CA QC OEL
		TWAEV (total dust)	0.2 mg/m3 (Manganese)	CA QC OEL
		TWA	0.5 mg/m3 (antimony)	CA BC OEL
		TWA (Respirable)	0.02 mg/m3 (Manganese)	CA BC OEL
		TWA (Total)	0.2 mg/m3 (Manganese)	CA BC OEL
		TWA	0.5 mg/m3 (antimony)	ACGIH
		TWA (Inhalable particulate matter)	0.1 mg/m3 (Manganese)	ACGIH
		TWA (Respirable	0.02 mg/m3 (Manganese)	ACGIH



ABS GP35 004.000% BEIGE 748SW-B

Page 5

Substance key: 000000645369	Revision Date: 09/19/2020
Version: 1 - 2 / CDN	Date of printing :05/02/2023

		particulate matter)		
C.I. Pigment Black 28	68186-91-4	TWA	1 mg/m3 (Copper)	NIOSH REL
C.I. Pigment White 6	13463-67-7	TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
Aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
		TWAEV (total dust)	10 mg/m3 (Aluminium)	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminium)	CA BC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH

Engineering measures

Use only in area provided with appropriate exhaust

ventilation.

Provide appropriate exhaust ventilation at machinery and at

places where dust can be generated.

Use engineering controls such as local or general exhaust to maintain airborne concentrations below exposure limits.

Personal protective equipment

Respiratory protection : Use NIOSH/MSHA approved respirators following

manufacturer's recommendations where dust or fume may be

generated.

Use respiratory protective equipment when using this product

at elevated temperatures (see section 8).

Hand protection

Remarks : Nitrile rubber gloves. Impervious butyl rubber gloves PVC

Neoprene gloves When handling hot material, use heat

resistant gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : Wear protective clothing, including long sleeves and gloves,

to prevent skin contact.

When handling hot melts use suitable protective clothing.

Hygiene measures : The usual Industrial Hygiene precautions must be taken

during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during

work intervals and after work.

Substance key: 000000645369



Page 6

ABS GP35 004.000% BEIGE 748SW-B

Revision Date: 09/19/2020

Version: 1 - 2 / CDN Date of printing: 05/02/2023

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Granules

Colour : brown

Odour : characteristic

Odour Threshold : Not applicable

pH : Not applicable

Melting point : > 90 °C

Boiling point : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : not determined

Self-ignition : Not applicable

Upper explosion limit / upper

flammability limit

not tested.

Lower explosion limit / Lower :

flammability limit

not tested.

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Relative density : not available

Density : not tested.

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

This property is not applicable for mixtures.

Decomposition temperature : To the best of our current knowledge, no thermal

decomposition of the product is expected if it is processed

according to good manufacturing practices. See section 10.4. "Conditions to avoid"



Page 7

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : no data available

no data available

Oxidizing properties : not available

Surface tension : Not relevant

Particle size : Product specific

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : To avoid thermal decomposition, do not overheat.

Heating can release hazardous gases.

Keep away from heat, sparks, open flames, and other sources

of ignition.

If small particles are generated during further processing, handling or by other means, may form combustible dust

concentrations in air.

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Keep away from heat and sources of ignition.

Incompatible materials : no data available

Strong acids and strong bases
Strong acids and oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

None known.

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate: 18.67 mg/l

Exposure time: 4 h



Page 8

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 3,720 mg/kg

Method: Calculation method

Components:

Aluminium oxide:

Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg

Method: OECD Test Guideline 401 GLP: No information available.

Acute inhalation toxicity : LC50 (Rat, male and female): > 2.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : Remarks: Not applicable

N,N'-Ethylenedi(stearamide):

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 6.3 mg/l

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

C.I. Pigment White 6:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg

Method: OECD Test Guideline 425

GLP: no

Acute inhalation toxicity : LC50 (Rat, male and female): 3.4 - 5.1 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: no

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: not required



ABS GP35 004.000% BEIGE 748SW-B

Page 9

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

Aluminium oxide:

Species: Rabbit Exposure time: 24 h

Method: OECD Test Guideline 404

Result: No skin irritation GLP: No information available.

N,N'-Ethylenedi(stearamide):

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

C.I. Pigment White 6:

Species: Rabbit Exposure time: 4 h

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: no

Serious eye damage/eye irritation

Product:

Result: No eye irritation

Components:

Aluminium oxide:

Result: Mild eye irritation

N,N'-Ethylenedi(stearamide):

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

C.I. Pigment White 6:

Species: rabbit eye Result: No eye irritation

Method: OECD Test Guideline 405 GLP: No information available.



Page 10

ABS GP35 004.000% BEIGE 748SW-B

Revision Date: 09/19/2020

Substance key: 000000645369 Version: 1-2/CDN Date of printing :05/02/2023

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

Aluminium oxide:

Test Type: Draize Test Exposure routes: Dermal Species: Guinea pig Method: Draize Test

Result: Not a skin sensitizer.

GLP: no

Test Type: Respiratory system

Exposure routes: inhalation (dust/mist/fume)

Species: Mouse Method: Other

Result: Not a skin sensitizer.

GLP: no

N,N'-Ethylenedi(stearamide):

Species: Mouse

Method: OECD Test Guideline 429 Result: Not a skin sensitizer.

C.I. Pigment White 6:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Dermal

Species: Mouse

Method: OECD Test Guideline 429 Result: Not a skin sensitizer. GLP: No information available.

Test Type: Buehler Test Exposure routes: Dermal Species: Guinea pig

Method: OECD Test Guideline 406 Result: Not a skin sensitizer.

GLP: yes

Test Type: Respiratory system

Exposure routes: inhalation (dust/mist/fume)

Species: Mouse Method: Other

Result: Does not cause respiratory sensitisation.

GLP: No information available.



ABS GP35 004.000% BEIGE 748SW-B

Page 11

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Germ cell mutagenicity

Components:

Aluminium oxide:

Genotoxicity in vitro : Test Type: In vitro gene mutation study in mammalian cells

Test system: mouse lymphoma cells Concentration: 6,1 - 780 μg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative GLP: yes

Remarks: By analogy with a product of similar composition

Genotoxicity in vivo : Test Type: Chromosome Aberration Test

Species: Rat (female)

Strain: wistar

Cell type: Bone marrow

Application Route: oral (gavage) Exposure time: Single exposure Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 475

Result: positive

GLP: No information available.

Test Type: Micronucleus test

Species: Rat (female)

Strain: wistar

Cell type: Bone marrow

Application Route: oral (gavage) Exposure time: Single exposure Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 474

Result: positive

GLP: No information available.

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

N,N'-Ethylenedi(stearamide):

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: Mammalian cell gene mutation assay

Test system: mouse lymphoma cells



Page 12

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Germ cell mutagenicity -

Assessment

In vitro tests did not show mutagenic effects

C.I. Pigment White 6:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium Concentration: 333 - 5000 µg/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test Type: Ames test

Test system: Escherichia coli Concentration: 333 - 5000 µg/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Strain: ICR

Cell type: Erythrocytes

Application Route: oral (gavage) Exposure time: single treatment Dose: 500 - 1000 - 2000 mg/kg Method: OECD Test Guideline 474

Result: negative

GLP: yes

Germ cell mutagenicity -

Assessment

In vitro tests did not show mutagenic effects, In vivo tests did

not show mutagenic effects

Carcinogenicity

Components:

Aluminium oxide:

Carcinogenicity - Assessment

Carcinogenicity classification not possible from current data.

N,N'-Ethylenedi(stearamide):

Carcinogenicity -

Assessment

No information available.

C.I. Pigment White 6:

Carcinogenicity - : Not classifiable as a human carcinogen.



Page 13

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Assessment

Reproductive toxicity

Components:

Aluminium oxide:

Effects on fertility : Species: Rat, male and female

Strain: Sprague-Dawley

Application Route: Drinking water Dose: 57 - 189 - 567 mg/kg

General Toxicity - Parent: NOAEL: ca. 567 mg/kg body weight General Toxicity F1: NOAEL: ca. 57 mg/kg body weight

Method: Other GLP: yes

Remarks: By analogy with a product of similar composition

Effects on foetal development

Species: Rat Strain: wistar

> Application Route: oral (gavage) Dose: 126 - 251 - 503 mg/kg Frequency of Treatment: 2 daily

General Toxicity Maternal: NOAEL: > 100 mg/kg body weight

Teratogenicity: NOAEL: 503 mg/kg body weight

Method: OECD Test Guideline 414 GLP: No information available.

Remarks: By analogy with a product of similar composition

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

No teratogenic effects to be expected.

N,N'-Ethylenedi(stearamide):

Effects on foetal development

Test Type: Pre-natal

Species: Rat

Strain: Sprague-Dawley

Application Route: oral (gavage)

General Toxicity Maternal: NOAEL: >= 1,000 mg/kg body

weight

Method: OECD Test Guideline 414

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

C.I. Pigment White 6:

Effects on fertility : Remarks: no data available

Effects on foetal development

: Test Type: Pre-natal Species: Rat, female

Strain: wistar

Application Route: oral (gavage) Dose: 100, 300, 1000 mg/kg bw Duration of Single Treatment: 14 d



ABS GP35 004.000% BEIGE 748SW-B

Page 14

Substance key: 000000645369 Revision Date: 09/19/2020 Version: 1-2/CDN Date of printing :05/02/2023

Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 1,000 mg/kg body weight Developmental Toxicity: NOAEL: 1,000 mg/kg body weight Embryo-foetal toxicity: NOEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Remarks: No significant adverse effects were reported

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility.

or on development, based on animal experiments. Did not show teratogenic effects in animal experiments.

STOT - single exposure

Components:

Aluminium oxide:

Target Organs: Lungs

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

N,N'-Ethylenedi(stearamide):

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

Aluminium oxide:

Target Organs: Lungs

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

N,N'-Ethylenedi(stearamide):

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

C.I. Pigment White 6:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.



ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Repeated dose toxicity

Components:

Aluminium oxide:

Species: Rat, male and female

NOAEL: 57 mg/kg

Application Route: Drinking water

Exposure time: 1 a

Number of exposures: continuously

Dose: 57 - 189 - 567 mg/kg

Group: yes

Method: OECD Test Guideline 426

GLP: yes

Remarks: By analogy with a product of similar composition

Species: Rat

LOAEL: 0.070 mg/l

Application Route: Inhalation

Exposure time: 6 m

Number of exposures: 6 hr/day; 5 days a week

Dose: 15-30-50-70-100 mg Al/m3 Method: OECD Test Guideline 413 GLP: No information available.

Application Route: Skin contact

Remarks: The study is not necessary from a scientific perspective.

N,N'-Ethylenedi(stearamide):

Species: Rat, male and female NOEL: >= 1000 mg/kg bw/day Application Route: oral (gavage) Method: OECD Test Guideline 408

C.I. Pigment White 6:

Species: Rat, male

NOEL: > 24000 mg/kg bw/day Application Route: oral (gavage)

Exposure time: 29 d Number of exposures: daily

Dose: 24000 mg/kg

Group: yes

Method: OECD Test Guideline 407 GLP: No information available.

Species: Rat, male and female

NOAEL: 0.01 mg/l

Application Route: Inhalation

Exposure time: 2 a

Number of exposures: 6 hours/day, 5 days/week

Dose: 0,0106 - 0,0507 - 0,250 mg/l

Group: yes

Method: Repeated Dose Toxicity (chronic Toxicity)

Page 15



ABS GP35 004.000% BEIGE 748SW-B

Page 16

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

GLP: no

Aspiration toxicity

Components:

Aluminium oxide:

No aspiration toxicity classification

N,N'-Ethylenedi(stearamide):

no data available

C.I. Pigment White 6:

No aspiration toxicity classification

Experience with human exposure

Product:

General Information : The possible symptoms known are those derived from the

labelling (see section 2).

Further information

Components:

C.I. Pigment White 6:

Remarks: Lung damage possible.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish :

Remarks: no data available

Components:

Aluminium oxide:

Toxicity to fish : NOEC (Salmo trutta (brown trout)): > 0.072 mg/l

Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 0.071 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202



Page 17

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

GLP: yes

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): >=

0.052 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

EC50 (Pseudokirchneriella subcapitata (green algae)): 1.05

mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

Remarks: By analogy with a product of similar composition

Toxicity to fish (Chronic

toxicity)

NOEC (Pimephales promelas (fathead minnow)): 56.48 mg/l

Exposure time: 7 d Test Type: semi-static test

Analytical monitoring: yes

Method: Other GLP: yes

Remarks: By analogy with a product of similar composition

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.076 mg/l

End point: Reproduction rate

Exposure time: 21 d Test Type: semi-static test Analytical monitoring: yes

Method: OECD Test Guideline 211

GLP: yes

Remarks: By analogy with a product of similar composition

Toxicity to microorganisms : Remarks: Not applicable

Toxicity to soil dwelling

organisms

Remarks: Not applicable

Plant toxicity : Remarks: Not applicable

Sediment toxicity : Remarks: Not applicable

Toxicity to terrestrial

organisms

: Remarks: Not applicable

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.



ABS GP35 004.000% BEIGE 748SW-B

Page 18

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

N,N'-Ethylenedi(stearamide):

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 0.027 mg/l

End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.0022 mg/l

Exposure time: 48 h Test Type: semi-static test

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (algae)): 0.053 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic

toxicity)

Remarks: no data available

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

EC50 (Daphnia magna (Water flea)): 0.0056 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: No toxicity at the limit of solubility

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h Test Type: static test

Method: OECD Test Guideline 209

Toxicity to soil dwelling

organisms

NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg

Exposure time: 56 d

Method: OECD Test Guideline 222

Sediment toxicity : NOEC: >= 1000 mg/kg dry weight (d.w.)

Test Type: static test Sediment: Artificial sediment Exposure duration: 28 d

Method: OECD Test Guideline 218

C.I. Pigment White 6:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h Test Type: static test Analytical monitoring: no

Method: EPA GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.



ABS GP35 004.000% BEIGE 748SW-B

Page 19

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Analytical monitoring: no

Method: OECD Test Guideline 203 GLP: No information available.

Remarks: The details of the toxic effect relate to the nominal

concentration.

LC50 (Cyprinodon variegatus (sheepshead minnow)): >

10,000 mg/l

Exposure time: 96 h Test Type: semi-static test

Analytical monitoring: no data available Method: OECD Test Guideline 203

GLP: ves

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to daphnia and other : aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Analytical monitoring: no data available Method: OECD Test Guideline 202

GLP: no data available

Remarks: The details of the toxic effect relate to the nominal

concentration.

LC50 (Acartia tonsa): > 10,000 mg/l

Exposure time: 48 h

Analytical monitoring: no data available Method: ISO 14669 and PARCOM method

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to algae/aquatic plants

EC50 (Pseudokirchneriella subcapitata (microalgae)): 61 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no

Method: EPA

GLP: No information available.

Remarks: The details of the toxic effect relate to the nominal

concentration.

EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l

End point: Growth rate Exposure time: 72 h

Analytical monitoring: no data available

Method: ISO 10253

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.



Page 20

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Toxicity to fish (Chronic

toxicity)

: LC50 (Oncorhynchus mykiss (rainbow trout)): 7.31 mg/l

Exposure time: 28 d Test Type: static test Analytical monitoring: yes

Method: Other

GLP: No information available.

Remarks: By analogy with a product of similar composition

Toxicity to microorganisms

EC50 (activated sludge of a predominantly domestic sewage):

> 1,000 mg/l

End point: Bacteria toxicity (respiration inhibition)

Exposure time: 3 h Test Type: aquatic

Method: OECD Test Guideline 209

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

NOEC (activated sludge of a predominantly domestic

sewage): >= 1,000 mg/l

End point: Bacteria toxicity (respiration inhibition)

Exposure time: 3 h Test Type: aquatic

Method: OECD Test Guideline 209

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to soil dwelling

organisms

Test Type: artificial soil

NOEC (Folsomia candida): 0,1 ->= 10 %

Exposure time: 28 d End point: mortality Method: ISO 11267

GLP: no

Remarks: By analogy with a product of similar composition This product does not have any known adverse effect on the

soil organisms tested.

Plant toxicity : NOEC: >= 10 %

Exposure time: 20 h End point: Growth

Species: Lactuca sativa (lettuce) Analytical monitoring: yes

Method: Other GLP: no

Remarks: By analogy with a product of similar composition

No effect on the growth was observed.

Sediment toxicity : NOEC (Hyalella azteca (Scud)): >= 100000 %

Analytical monitoring: no Sediment: artificial soil Exposure duration: 28 d Nominal / Measured: nominal



Page 21

ABS GP35 004.000% BEIGE 748SW-B

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Basis for effect: mortality

Method: Other GLP: no

Remarks: By analogy with a product of similar composition

NOEC: >= 14989 mg/kg dry weight (d.w.) Analytical monitoring: no data available

Sediment: Natural sediment Exposure duration: 10 d Nominal / Measured: nominal Basis for effect: mortality

Method: Other GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Components:

Aluminium oxide:

Biodegradability : Remarks: Not applicable

N,N'-Ethylenedi(stearamide):

Biodegradability : aerobic

Inoculum: activated sludge Carbon dioxide (CO2)

Result: Not readily biodegradable.

Biodegradation: 5.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

C.I. Pigment White 6:

Biodegradability : Remarks: Not applicable for inorganic compound.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: not tested.

Components:

Aluminium oxide:

Bioaccumulation : Remarks: Not applicable

N,N'-Ethylenedi(stearamide):

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

Remarks: Not applicable



ABS GP35 004.000% BEIGE 748SW-B

Page 22

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

C.I. Pigment White 6:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 20 - 200

Exposure time: 14 d Concentration: 0.1 - 1 mg/l

Method: Other

GLP: No information available.

Remarks: Does not accumulate in organisms.

Partition coefficient: n-

octanol/water

Remarks: inorganic

Mobility in soil

Product:

Distribution among :

environmental compartments

Remarks: not tested.

Components:

Aluminium oxide:

Distribution among

Remarks: Not applicable

environmental compartments

N,N'-Ethylenedi(stearamide):

Distribution among : log Koc: 8.6 - 8.91 environmental compartments Method: calculated

C.I. Pigment White 6:

Mobility : Remarks: Adsorption to solid soil phase is possible.

Distribution among : Ad environmental compartments Me

Adsorption/Soil Medium: water - soil

log Koc: 4.61 Method: Other

Other adverse effects

Product:

Results of PBT and vPvB

assessment

Remarks: No information is available as no chemical safety

report (CSR) is required.

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

Components:

Aluminium oxide:

Environmental fate and

pathways

not available



ABS GP35 004.000% BEIGE 748SW-B

Page 23

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Results of PBT and vPvB

assessment

: Remarks: Not applicable

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

N,N'-Ethylenedi(stearamide):

Results of PBT and vPvB

assessment

The substance is not identified as a PBT or as a vPvB

substance.

C.I. Pigment White 6:

Environmental fate and

pathways

: not available

Results of PBT and vPvB

assessment

This substance is not considered to be persistent,

bioaccumulating and toxic (PBT).

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of this product in accordance with all applicable local,

state and federal regulations.

Contaminated packaging : Regulations concerning reuse or disposal of used packaging

materials must be observed.

SECTION 14. TRANSPORT INFORMATION

TDG not restricted
IATA not restricted
IMDG not restricted

SECTION 15. REGULATORY INFORMATION

NPRI Components : Zinc compounds

Antimony compounds
Manganese Compound
Chromium (III) compound
Copper Compound

The components of this product are reported in the following inventories:



ABS GP35 004.000% BEIGE 748SW-B

Page 24

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and

safety, Schedule 1, Part 1: Permissible exposure values for

airborne contaminants

NIOSH REL : USA. NIOSH Recommended Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average CA AB OEL / TWA : 8-hour Occupational exposure limit CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations



ABS GP35 004.000% BEIGE 748SW-B

Page 25

 Substance key: 000000645369
 Revision Date: 09/19/2020

 Version: 1 - 2 / CDN
 Date of printing: 05/02/2023

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 09/19/2020 Date format : mm/dd/yyyy

The information contain herein is accurate to the best knowledge of Avient Corporation and its subsidiaries and affiliates. However, neither Avient nor any of its subsidiaries or affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of the Avient product is the sole responsibility of the user. Any material may present unknown hazards and should be used with caution. Due to possible changes in Avient products and applicable national and international regulations and laws, the status of the products could change. Although certain hazards are described herein, Avient and its subsidiaries and affiliates cannot guarantee that these are the only hazards that exist. This information is only valid for the current intended use, and is not valid for such Avient product used in conjunction with any other materials or in any process.

CA / EN