

LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 1

Substance key: 000000793599	Revision Date: 05/09/2019
Version: 1 - 0 / USA	Date of printing :05/09/2019

SECTION 1. IDENTIFICATION

Identification of the

company:

MB, West Chicago

4000 Monroe Road Charlotte, NC, 28205

Telephone No.: +1 704-331-7000

Information of the substance/preparation:

BU Masterbatches

Product Stewardship +1-704-331-7710

Emergency tel. number: +1 800-424-9300(CHEMTREC)

Trade name: LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Material number: FZ94687263

Chemical family: Colourant preparation

Primary product use: Additive for plastic material processing

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 2

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Storage:

P405 Store locked up.

Other hazards

Hazards Not Otherwise Classified: No particular hazards known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Colourant preparation

Components

Chemical name	CAS-No.	Concentration (% w/w)
Zinc distearate	557-05-1	1 - 5
C.I. Pigment Black 7	1333-86-4	10 - 30

Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Ensure that the First Aid Personnel are aware of the product

involved, and take precautions to protect themselves (e.g.

wear personal protection equipment).

Get medical advice/attention if you feel unwell.

If inhaled : Move the victim to fresh air.

Give oxygen or artificial respiration if needed. Get immediate medical advice/ attention.

Never give anything by mouth to an unconscious person.

In case of skin contact : Remove contaminated clothing and shoes.

Wash off immediately with plenty of water for at least 15

minutes.

Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Get medical attention immediately if irritation develops and

persists.

If swallowed : Rinse mouth.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

Get medical advice/ attention.

Most important symptoms and effects, both acute and

delayed

The possible symptoms known are those derived from the

labelling (see section 2).

No additional symptoms are known.



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 3

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Notes to physician : Aspiration hazard if swallowed - can enter lungs and cause

damage.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Sulphur oxides Aldehydes Formaldehyde Metal oxides Carbon oxides

Further information : Combustible material

In the event of fire and/or explosion do not breathe fumes. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion

Do not allow run-off from fire fighting to enter drains or water

courses.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for firefighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Refer to protective measures listed in sections 7 and 8.

Avoid contact with skin, eyes and clothing.

Wash thoroughly after handling.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent product from entering drains.

Methods and materials for containment and cleaning up

Prevent product from entering drains. Non-sparking tools should be used.

Take measures to prevent the build up of electrostatic charge. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 4

Substance key: 000000793599	Revision Date: 05/09/2019
Version: 1 - 0 / USA	Date of printing :05/09/2019

Clean contaminated surface thoroughly.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Take measures to prevent the build up of electrostatic charge.

Handle in accordance with good industrial hygiene and safety Advice on safe handling

practice.

Use only with adequate ventilation/personal protection.

For personal protection see section 8. Avoid contact with skin, eyes and clothing.

Use only with adequate ventilation.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Keep away from heat, sparks and open flames. Store in proper container and keep container closed when not in use.

Conditions for safe storage Keep container tightly closed in a cool, well-ventilated place.

Protect from moisture.

Keep away from direct sunlight.

Further information on

storage conditions

Store in a cool, dry, well-ventilated area. Keep container

sealed when not in use.

Store away from flammable or combustible materials.

Keep in an area equipped with sprinklers.

Keep from freezing.

Materials to avoid not required

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
C.I. Pigment Black 7	1333-86-4	TWA (Inhalable fraction)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
Zinc distearate	557-05-1	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 5

Substance key: 000000793599	Revision Date: 05/09/2019
Version: 1 - 0 / USA	Date of printing :05/09/2019

TWA (total dust)	15 mg/m3	OSHA Z-1
TWÁ	5 mg/m3	OSHA Z-1
(respirable fraction)		
TWA (Total	10 mg/m3	OSHA P0
dust)		
TWA	5 mg/m3	OSHA P0
(respirable		
dust fraction)		
TWA	10 mg/m3	ACGIH
(Inhalable		
fraction)		
TWA	3 mg/m3	ACGIH
(Respirable		
fraction)		

Engineering measures : Use engineering controls such as local or general exhaust to

maintain airborne concentrations below exposure limits.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal use. Use

NIOSH/MSHA approved respirators following manufacturer's recommendations where dust, mist, or spray mist may be

generated.

Hand protection

Remarks : Nitrile rubber gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : Wear protective clothing, including long sleeves and gloves,

to prevent skin contact.

Hygiene measures : The usual Industrial Hygiene precautions must be taken

during work, in particular: do not drink, eat or smoke during the handling of the product and clean hands and face during

work intervals and after work.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid

Colour : black

Odour : characteristic

Odour Threshold : Not applicable

pH : not tested.

Melting point : Not applicable



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 6

Substance key: 000000793599 Revision Date: 05/09/2019 Version: 1-0/USA Date of printing:05/09/2019

Boiling point not determined

Flash point not tested.

Evaporation rate not tested.

Flammability (solid, gas) Not applicable

Self-ignition not tested.

Upper explosion limit / upper

flammability limit

not tested.

Lower explosion limit / Lower : not tested.

flammability limit

Vapour pressure not tested.

Relative vapour density Not applicable

Relative density not available

Density approx. 1 g/cm3

Value determined from data on raw material.

Solubility(ies)

Water solubility not determined

Partition coefficient: n-

octanol/water

This property is not applicable for mixtures.

Decomposition temperature To the best of our current knowledge, no thermal

decomposition of the product is expected if it is processed

according to good manufacturing practices. See section 10.4. "Conditions to avoid"

Viscosity

Viscosity, dynamic not tested.

Viscosity, kinematic not tested.

Explosive properties no data available

no data available

Oxidizing properties : not available

Surface tension not tested.

Particle size Product specific



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 7

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : Keep away from heat, sparks, open flames, and other sources

of ignition.

Incompatible materials : Strong oxidizing agents

Fluorine Peroxides

Strong acids and oxidizing agents Strong acids and strong bases

Oxidizing agents

Hazardous decomposition

products

No decomposition if used as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

C.I. Pigment Black 7:

Acute oral toxicity : LD50 (Rat, male and female): > 10,000 mg/kg

Method: OECD Test Guideline 401

GLP: no

Remarks: No significant adverse effects were reported

Acute inhalation toxicity : LC0 (Rat): > 0.0046 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: No information available.

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : Remarks: not required



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 8

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Skin corrosion/irritation

Product:

Result: No skin irritation

Components:

C.I. Pigment Black 7:

Species: Rabbit

Exposure time: 4 - 24 h

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: no

Serious eye damage/eye irritation

Product:

Result: No eye irritation

Components:

C.I. Pigment Black 7:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: no

Respiratory or skin sensitisation

Product:

Result: non-sensitizing

Components:

C.I. Pigment Black 7:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406 Result: Not a skin sensitizer.

Nesult. Not a skill sellsi

GLP: yes

Germ cell mutagenicity

Components:

C.I. Pigment Black 7:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 9

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

GLP: yes

Test Type: In vitro gene mutation study in mammalian cells

Test system: Rodent cell line Metabolic activation: without Method: OECD Test Guideline 476

Result: positive

GLP: No information available.

Test Type: Micronucleus test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

GLP: yes

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Components:

C.I. Pigment Black 7:

Carcinogenicity - Assessment

: Not classifiable as a human carcinogen.

IARC Listed

OSHA Listed

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Components:

C.I. Pigment Black 7:

Effects on foetal : Test Type: Pre-natal

development Species: Rabbit, male and female

Strain: New Zealand white
Application Route: Inhalation
Dose: 10% diesel exhaust emission
Duration of Single Treatment: 12 d
Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

GLP: no

Remarks: By analogy with a product of similar composition

Reproductive toxicity -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 10

Substance key: 000000793599	Revision Date: 05/09/2019
Version: 1 - 0 / USA	Date of printing :05/09/2019

STOT - single exposure

Components:

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

C.I. Pigment Black 7:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

C.I. Pigment Black 7:

Species: Rat, female NOAEL: 52 mg/kg bw/day Application Route: oral (feed) Exposure time: 1 a - 2 a Number of exposures: daily Dose: 2,05 g/kg of chow diet

Group: yes Method: Other

GLP: No information available.

Remarks: No adverse effect has been observed in chronic toxicity tests.

Species: Rat, male NOAEL: 0.0011 mg/l LOAEL: 0.0071 mg/l Application Route: Inhalation Test atmosphere: dust/mist Exposure time: 13 w

Number of exposures: 6 h per day; 5 d per week

Dose: 1,1 - 7,1 - 52,8 mg/m3

Group: yes Method: Other

GLP: No information available.

Species: Mouse, male and female Application Route: Skin contact

Exposure time: 12-18 m

Number of exposures: 3 times per week Dose: 20% carbon black suspensions

Group: yes Method: Other GLP: no

Remarks: No adverse effect has been observed in chronic toxicity tests.



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 11

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Aspiration toxicity

Components:

C.I. Pigment Black 7:

No aspiration toxicity classification

Experience with human exposure

Product:

General Information : The possible symptoms known are those derived from the

labelling (see section 2).

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: no data available

Components:

C.I. Pigment Black 7:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l

End point: mortality Exposure time: 96 h Test Type: semi-static test Analytical monitoring: no

Method: OECD Test Guideline 203

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 5,600 mg/l End point: Immobilization

Exposure time: 24 h
Test Type: static test
Analytical monitoring: no

Method: OECD Test Guideline 202

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: no

Method: OECD Test Guideline 201



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 12

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

GLP: yes

Remarks: The details of the toxic effect relate to the nominal

concentration.

Toxicity to fish (Chronic

toxicity)

Remarks: not required

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

Remarks: not required

Toxicity to microorganisms : EC0 (activated sludge): > 400 mg/l

End point: Bacteria toxicity (growth inhibition)

Exposure time: 3 h Test Type: static test Method: DIN 38412

GLP: no

Toxicity to soil dwelling

organisms

Test Type: Other Method: Other

GLP: No information available.

Remarks: This product does not have any known adverse

effect on the soil organisms tested.

Persistence and degradability

Components:

C.I. Pigment Black 7:

Biodegradability : Remarks: Not applicable

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: not tested.

Components:

C.I. Pigment Black 7:

Bioaccumulation : Remarks: Not applicable

Mobility in soil

Product:

Distribution among environmental compartments

Remarks: not tested.

Components:

C.I. Pigment Black 7:

Distribution among : Adsorption/Soil environmental compartments Medium: water - soil



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 13

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Remarks: Not applicable

Other adverse effects

Product:

Results of PBT and vPvB

assessment

Remarks: No information is available as no chemical safety

report (CSR) is required.

Additional ecological

information

Do not allow to enter ground water, waterways or waste water.

Components:

C.I. Pigment Black 7:

Environmental fate and

pathways

not available

Results of PBT and vPvB

assessment

The substance is not identified as a PBT or as a vPvB

substance.

Additional ecological

information

: Do not allow to enter ground water, waterways or waste water.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of this product in accordance with all applicable local,

state and federal regulations.

Contaminated packaging : Regulations concerning reuse or disposal of used packaging

materials must be observed.

SECTION 14. TRANSPORT INFORMATION

DOT not restrictedIATA not restrictedIMDG not restricted

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazards : Germ cell mutagenicity

Carcinogenicity



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 14

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Zinc distearate 557-05-1 3 %

Clean Water Act

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307, Zinc

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory, All components are compliant with the

TSCA Inventory Notification (Active) rule.

TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals: No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D): No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing



LQ ABS KUHMO 775 001.000% BLACK BC11040 LC

Page 15

 Substance key: 000000793599
 Revision Date: 05/09/2019

 Version: 1 - 0 / USA
 Date of printing: 05/09/2019

Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified: NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/09/2019

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application. NO EXPRESS OR IMPLIED WARRANTY IS MADE OF THE MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE OF ANY PRODUCT OR SERVICE. Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

US / EN