

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 1 / 10

01 Identification of the substance/mixture and of the company undertaking

• 1.1 Product identifier

- Trade name:
SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883
- Article number:
410883

Intended use:

Industrial applications

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Not determined.
- Application of the substance / the preparation

• 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:
WEILBURGER Coatings GmbH
Ahäuserweg 12-22
D-35781 Weilburg
Telefon: 00496471 315-0
Fax : 00496471 315-116

- * Further information obtainable from:
- * Product safety department. Tel. +49 (0) 6471 315 177 Fax +49 (0) 6471 315 5177 E-Mail: SDS-Info@weilburger.com
- * 1.4 Emergency telephone number:
(Carechem 24): Europe:+44 1235 239670 / Germany:+49 89 220 61012 / Middle East/Africa:+44 1235 239671 / Middle East (arabic language):+44 1273 289454 / America:+1 215 207 0061 / Brazil:+55 11 3197 5891 / East Asia/South East Asia (without China):+65 3158 1412

02 Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2 - H315 Causes skin irritation.
Eye Irrit. 2 - H319 Causes serious eye irritation.
Skin Sens. 1 - H317 May cause an allergic skin reaction.



GHS09

Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

(continued on page 2)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 2 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 1)



GHS07 GHS09

- Signal word
Warning

- Hazard-determining components of labelling:
hexamethylene diacrylate / bisphenol A diglycidylether diacrylat (BADGE-DA)
- Hazard statements
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P302+P352 IF ON SKIN: Wash with plenty of water.
P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT:
Not applicable.
- vPvB:
Not applicable.

03 Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- Description:
Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

*	CAS Number		%
	13048-33-4	hexamethylene diacrylate EC number: 235-921-9 Record number 01-2119484737-22-XXXX ⚠ Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, Skin Sens. 1 - H317; ⚠ Aquatic Acute 1 - H400, Aquatic Chronic 2 - H411	10,01- 25,00
	55818-57-0	bisphenol A diglycidylether diacrylat (BADGE-DA) EC number: 500-130-2 Record number 01-2119490020-53-XXXX ⚠ Skin Sens. 1 - H317; Aquatic Chronic 4 - H413	2,51- 10,00

(continued on page 3)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31




19788001

Reviewed on: 26.03.2020

Page : 3 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 2)

51728-26-8	Pentaerythritol, Ethoxylated, Esters with Acrylic Acid	25,01- 50,00
	 Skin Irrit. 2 - H315, Eye Irrit. 2 - H319;  Aquatic Chronic 2 - H411	
7473-98-5	2-hydroxy-2-methylpropiophenone	2,51- 10,00
	EC number: 231-272-0 Record number 01-2119472306-39-XXXX  Acute Tox. 4 - H302	

04 First aid measures

- 4.1 Description of first aid measures
- General information:**
In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- After inhalation:**
Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
- After skin contact:**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.
- After eye contact:**
Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.
- After swallowing:**
If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
- Information for doctor:**
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

05 Firefighting measures

- 5.1 Extinguishing media**
- Suitable extinguishing agents:**
alcohol resistant foam, CO₂, powder, water spray/mist
- For safety reasons unsuitable extinguishing agents:**
water jet
- 5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- 5.3 Advice for firefighters**
- Protective equipment:
Appropriate self-contained breathing apparatus may be required.
- Additional information**
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.

GB

(continued on page 4)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 4 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 3)

06 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.
- **6.2 Environmental precautions:**
Do not allow to enter drains or water courses. If the product enters drains or sewewrs the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.
- **6.3 Methods and material for containment and cleaning up:**
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean preferably with a detergent; avoid the use of solvents.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.

*

07 Handling and storage

- **Handling:**
- **7.1 Precautions for safe handling**
Exclude sources of heat, sparks and open flames. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed airfed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Keep the container tightly closed. Never use pressure to empty: the container is not a pressure vessel. No smking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage.
- **Information about storage in one common storage facility:**
Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
- **Further information about storage conditions:**
Always keep in containers made of the same material as the supply container. Observe the label precautions. Store between 5 and 30°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.
- **Storage class:**
12
- **7.3 Specific end use(s)**
No further relevant information available.

08 Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
- **Additional information:**
The lists that were valid during the creation were used as basis.

(continued on page 5)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 5 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 4)

- 8.2 Exposure controls
- **Personal protective equipment:**
- General protective and hygienic measures:
All parts of the skin should be washed after contact.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Short term filter device: Filter A/P2 Air-fed respiratory protective equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the occupational exposure limit and engineering controls and methods cannot reasonably be improved.
- Protection of hands: To avoid skin problems reduce the wearing of gloves to the required minimum. Avoid direct contact with the chemical/ the product/ the preparation by organisational measures. Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability. If only a short-term loading of the glove material by splashes is expected, tricoted gloves with higher wearability for the better acceptance of the users are recommended. Solvent resistant gloves
- Material of gloves
- Penetration time of glove material
- Eye protection: Tightly sealed eye protection designed to protect against liquid splashes should be worn.
- Body protection: Cotton or cotton/synthetic overalls or coveralls are normally suitable.

09 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Transparent
Odour:	Specific type
Odour threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Initial boiling point and boiling range:	101 °C
Flash point:	>= 101 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.

(continued on page 6)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 6 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 5)

</

10 Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- **Conditions to be avoided:**
Staple under the recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions
No dangerous reactions known.
- 10.4 Conditions to avoid
No further relevant information available.
- * • **10.5 Incompatible materials:**
No further relevant information available.
- * • **10.6 Hazardous decomposition products:**
In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen may be produced.

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- LD/LC50 values relevant for classification:
- 13048-33-4 **hexamethylene diacrylate**
Oral, LD50: >5000 mg/kg (rat) Dermal, LD50: 3650 mg/kg (Rabbit) Oral, LD50: >2000 mg/kg (rat)
Dermal, LD50: >2000 mg/kg (rat) Oral, LD50: 1694 mg/kg (rat) Dermal, LD50: 6929 mg/kg (rat)
- 55818-57-0 **bisphenol A diglycidylether diacrylat (BADGE-DA)**
- 7473-98-5 **2-hydroxy-2-methylpropiophenone**
- Primary irritant effect:
- Skin corrosion/irritation
Irritant to skin and mucous membranes.
- Serious eye damage/irritation
Irritating effect.
- Respiratory or skin sensitisation
Sensitization possible through skin contact.

(continued on page 7)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 7 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 6)

- **Practical knowledge**

Other observations:

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

General comment:

There is no data available on the product itself.

12 Ecological information

There is no data available on the product itself. The product should not to be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

- **12.1 Toxicity**
- Aquatic toxicity:
No further relevant information available.
- **12.2 Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- **12.3 Bioaccumulative potential**
No further relevant information available.
- **12.4 Mobility in soil**
No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT:
Not applicable.
- vPvB:
Not applicable.
- **12.6 Other adverse effects**
No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation
After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste. Do not allow into drains or water courses or dispose of where ground or surface waters may be effected.
- **Uncleaned packaging:**
- Recommendation:
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

- **14.1 UN-Number**

ADR	UN3082
IMDG	UN3082
IATA	UN3082

(continued on page 8)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 8 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 7)

• **14.2 UN proper shipping name**

ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(PENTAERYTHRITOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(PENTAERYTHRITOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID)


IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(PENTAERYTHRITOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID)

• **14.3 Transport hazard class(es)**

ADR

Class 9 Miscellaneous dangerous substances and articles.

Label




IMDG

Class

9 Miscellaneous dangerous substances and articles.

Label




IATA

Class

9 Miscellaneous dangerous substances and articles.

Label



• **14.4 Packing group**

ADR III

IMDG III

IATA III

• **14.5 Environmental hazards:**

Marine pollutant: Yes

• **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

Danger code (Kemler): 90

EMS Number: F-A,S-F

• **14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

• **Transport/Additional information:**

Not applicable.

(continued on page 9)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 9 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 8)

Excepted quantities (EQ): E1

Limited quantities (LQ) 5L

Transport category 3

Tunnel restriction code E

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) E1

• **UN "Model Regulation":**

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(PENTAERYTHRITOL, ETHOXYLATED, ESTERS WITH ACRYLIC ACID), 9, III

15 Regulatory information

• **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

• **REGULATION (EC) No 1907/2006 ANNEX XVII**

* Conditions of restriction: 3

• **National regulations:**

• **Waterhazard class:**

Water hazard class 3 (Self-assessment): extremely hazardous for water.

• **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this safety data sheet is provided in accordance with the requirements of the CHIP regulation. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the suppliers's control, the user is responsible for ensuring that the requirements of relevant legislation

* • **Relevant phrases**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

* H319 Causes serious eye irritation.

* H400 Very toxic to aquatic life.

* H411 Toxic to aquatic life with long lasting effects.

* H413 May cause long lasting harmful effects to aquatic life.

• **Department issuing MSDS:**

Product safety department.

* • **Contact:**

* Tel. +49 (0) 6471 315 177 Fax +49 (0) 6471 315 5177 email: SDS-Info@weilburger.com

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(continued on page 10)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

19788001

Reviewed on: 26.03.2020

Page : 10 / 10

PRODUCT : SENOPOL®-UV-Kantenbandlack farblos 07-3280-410883

(continued of page 9)

- IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
- * Data compared to the previous version altered.